

ProFill 1 and ProFill 2

The Premier 1 & 2 Product Sink Dispensers

ProFill sets a new standard in performance in sink dispensing with greater reliability, durability and easier serviceability in a more compact size. ProFill's attractive ergonomic design takes up less wall space yet provides more label space for product identification and operating instructions. And like all Dema products, ProFill is designed to lower your total cost of ownership with an all metal manifold for greater durability and an easy to remove front cover for faster on wall serviceability.



- Attractive stainless steel cover has increased space for product labeling and operating instructions
- Smaller overall size takes up less wall space
- Easy fast access to service without removing unit from wall
- All brass and stainless steel manifold for greater durability and reliability
- Water inlet is easy to switch from left to right side
- Separate models for single or dual water sources, action gap or air gap backflow devices and single or dual chemicals

MODELS / OPTIONS

PF651GAP	1 product system with action gap backflow preventer
PF651AG	1 product system with air gap backflow preventer
*PF652GAP	2 product system with action gap backflow preventers
*PF652AG	2 product system with air gap backflow preventers

SPECIFICATIONS

Dilution ratios	1:7 to 1:1090**	
Operating Pressure Range	20-125 psi	1.38-8.62 bar
Environmental Temp	32- 150°F	0-65.5°C
Flow rates:	4 gallons/min.	15.1 liters/min.

*Available with 2 water sources as (part #-)2M

**Actual dilution range is dependent on product viscosity. Leaner dilutions can be achieved with ultra lean metering devices

