



INDUSTRIAL SOLUTIONS: HIGH PRESSURE MANIFOLDS

PILOT-PISTON MANIFOLD VALVES

The 456/8M series is a forged stainless steel manifold with innovative features like a maintenance cavity for easy servicing and mounting holes to facilitate panel mounting. These are available in 2 and 3-station variations with normally closed and normally open options. The inlets and outlets range in size from 3/4" to 1", with coils available for 24 VDC, 24 VAC, and 120VAC.

About

- Available in 2 & 3 station
- Normally closed or normally open configurations
- 24V AC, 24V DC, and 120V coils available
- 3/4" - 1" NPT Inlet and Outlet
- 1200PSI MOPD
- CV = 3.0

Features & Benefits

- Stainless steel forged body / Piston / Sleeve / Seat
- Maintenance cavity for access to internal components
- Mounting holes for panel mounting



PART	# OF STA.	OP. MODE	OP. MODE	OP. MODE	INLET	OUTLET	VOLTAGE
456M2.6.CC.3D	2	N/C	N/C	--	3/4" NPT	3/4" NPT	24 VAC
456M2.6.CC.4D	2	N/C	N/C	--	3/4" NPT	3/4" NPT	24 VDC
456M2.6.CC.6D	2	N/C	N/C	--	3/4" NPT	3/4" NPT	120 VAC
456M2.6.OC.3D	2	N/O	N/C	--	3/4" NPT	3/4" NPT	24 VAC
456M2.6.OC.4D	2	N/O	N/C	--	3/4" NPT	3/4" NPT	24 VDC
456M2.6.OC.6D	2	N/O	N/C	--	3/4" NPT	3/4" NPT	120 VAC
456M3.4.CCC.4D	3	N/C	N/C	N/C	3/4" NPT	1/2" NPT	24 VDC
456M3.4.OCC.4D	3	N/O	N/C	N/C	3/4" NPT	1/2" NPT	24 VDC
456M3.4.OOO.4D	3	N/O	N/O	N/O	3/4" NPT	1/2" NPT	24 VDC
456M3.6.CCC.3D	3	N/C	N/C	N/C	3/4" NPT	3/4" NPT	24 VAC
456M3.6.CCC.4D	3	N/C	N/C	N/C	3/4" NPT	3/4" NPT	24 VDC
456M3.6.CCC.6D	3	N/C	N/C	N/C	3/4" NPT	3/4" NPT	120 VAC
458M2.8.CC.3D	2	N/C	N/C	--	1" NPT	1" NPT	24 VAC
458M2.8.CC.6D	2	N/C	N/C	--	1" NPT	1" NPT	120 VAC
458M2.8.OC.3D	2	N/O	N/C	--	1" NPT	1" NPT	24 VAC
458M2.8.OC.4D	2	N/O	N/C	--	1" NPT	1" NPT	24 VDC
458M2.8.OC.6D	2	N/O	N/C	--	1" NPT	1" NPT	120 VAC
458M2.8.OO.4D	2	N/O	N/O	--	1" NPT	1" NPT	24 VDC
458M2.8.OO.6D	2	N/O	N/O	--	1" NPT	1" NPT	120 VAC

DEMA Engineering Company

10020 Big Bend Road
St. Louis, MO 63122 U.S.A

Tel: 314-966-3533
Fax: 314-965-8319

demaeng.com

sales@demaeng.com