

Model X12

2 YEAR WARRANTY

X-MARK® or SMART MARK® XEPTOR®
THE SMART MULTI-COIN AND ENCODED TOKEN ACCEPTORS



IDX's X12 series of multi-coin Xeptors® will accept a mixture of 6 different coins. This coin mixture can consist of any combination of currencies, tokens and X-Mark® or Smart Mark® encoded security tokens. The X10 Xeptors® has internal programming to allow the operator the ability to program new coins, change the number of coin pulses per coin and field self-diagnostic information. Coin pulses are released through a shielded relay to offer the OEM an easier interface for multiple coin voltage requirements. Other coin outputs are available to meet the different demands of the OEMs. All modes come standard with coin sense / anti-straning optics for added security. This smart thinking Xeptor® continues up date its memory on each coin as the Xeptor® ages.

Digging coin jams out is a thing of the past. The built in coin release opens the chute to drop through bent and mutilated coins. Coin jams are also caused where bent faceplates are miss alignment with the Xeptors® faceplate to meter doors. This has been eliminated with the introduction of a new all stainless steel snap in faceplate model MA19 which relieves the strain from bent doors.

X12 XEPTOR® SERIES FEATURES: STANDARD 2 YEAR WARRANTY

- Standard Preprogrammed with U.S. Quarter and U.S. Dollar coins can be field changed.
- Standard 4 wire hookup – Power wires –Yellow 24VAC Hot / Black 24VAC Common – Coin wires (2) Red Green.
- Power sources 24 VAC OR 24VDC standard optional voltages – 12VDC
- Distinguishes and accepts any of up to (6) six different coins, tokens, X-Mark®, or Smart Mark® encoded tokens of different sizes and/or different electronic signatures.
- Standard 2" faceplate footprint The Snap in Stainless Steel faceplate model #MA19.
- Optional old style faceplate model # MA20.
- Diameter range examples: 0.700" - 1.073" (17.8 mm to 27.3mm)/ 0.900" - 1.125" (22.8 mm to 28.6mm).
- Thickness range settings: 0.087" to 0.130" (Canadian Dime 1.22mm to British 1£ 3.15mm).
- Slide on water resistant access covers.
- Built-in "Credit Test" push button.
- New coin types can be learned or programmed in the field.
- Unwanted shadow coin feature eliminates false acceptance of undesired coins.
- Multi-color indicator LED for operational status.
- Credit sense optics standard for extra security.
- Optional programmable multi-denominational diverter controls direction for presorting coins.
- Patent Coverage: U.S.#5,046,841 U.S.#6,021,882 U.K.#2,227,347 U.K.#8,929,131 U.K.#9,905,044 U.K.#2,335,207 Aus.#619,639 Aus.#1,952,499 Aus.#4,788,290 Can.#1,313,806 Jap. #9471,1990 Grm.#4,000,197 Others Pending

1812 Lorene St, El Dorado, AR 71730 USA

☎ 800-643-1109, 870-862-2051, FAX 870-862-3472 e-mail: sales@idxinc.com , web site: www.idxinc.com