



## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 11.13.2019

Page 1 of 13

**Revision date:** 04.06.2020

### Ceramic Finish Clear Coat

#### SECTION 1: Identification

##### Product identifier

**Product name:** Ceramic Finish Clear Coat

**Product code:** 10-CC-5

##### Recommended use of the product and restriction on use

**Relevant identified uses:** Protectant Wax/Sealer

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

##### Manufacturer or supplier details

###### Manufacturer:

###### United States

JBS Industries

2550 Henkle Drive

Lebanon, Ohio 45036

513-228-2800

SBAETEN@JBSINDUSTRIES.COM

##### Emergency telephone number:

###### North America

CHEMTREC

800-424-9300 (24 hours)

#### SECTION 2: Hazard(s) identification

##### GHS classification:

Skin irritation, category 2

Serious eye damage, category 1

Flammable liquids, category 3

Reproductive toxicity, category 2

Specific target organ toxicity - single exposure, category 3, narcotic effects

##### Label elements

###### Hazard pictograms:



**Signal word:** Danger

##### Hazard statements:

H226 Flammable liquid and vapor

H361 Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 11.13.2019

Page 2 of 13

Revision date: 04.06.2020

## Ceramic Finish Clear Coat

H336 May cause drowsiness or dizziness

H315 Causes skin irritation

H318 Causes serious eye damage

### Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment

P242 Use only non-sparking tools

P280 Wear protective gloves/protective clothing/eye protection/face protection

P202 Do not handle until all safety precautions have been read and understood

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash hands thoroughly after handling

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P308+P313 IF exposed or concerned: Get medical advice/attention

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P302+P352 IF ON SKIN: Wash with plenty of water

P332+P313 If skin irritation occurs: Get medical advice/attention

P362 Take off contaminated clothing and wash it before reuse

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P403+P235 Store in a well-ventilated place. Keep cool

P405 Store locked up

P501 It is the responsibility of the waste generator to characterize all waste material according to regulatory entities.

**Hazards not otherwise classified:** None

## SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 64741-44-2	Distillates (petroleum), straight-run middle	5-25
CAS number: 111-76-2	2-Butoxyethanol	5-30
CAS number: 67-63-0	Propan-2-ol	1-5
CAS number: 61789-77-3	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	1-15
CAS number: 84133-50-6	Alcohols, C12-14-secondary, ethoxylated	1-5

**Additional Information:** None

## SECTION 4: First aid measures

### Description of first aid measures

#### General notes:

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 11.13.2019

Page 3 of 13

Revision date: 04.06.2020

## Ceramic Finish Clear Coat

Show this Safety Data Sheet to the doctor in attendance.

### After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

### After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

### After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

### After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

## Most important symptoms and effects, both acute and delayed

### Acute symptoms and effects:

Product is highly flammable. Exposure to sources of ignition may cause physical injury.  
Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness.  
Skin contact may result in redness, pain, burning and inflammation.  
Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

### Delayed symptoms and effects:

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.  
Effects are dependent on exposure (dose, concentration, contact time).

## Immediate medical attention and special treatment

### Specific treatment:

Overexposure via inhalation requires urgent medical treatment.  
In case of eye contact, seek prompt medical attention while rinsing is continued.

### Notes for the doctor:

Treat symptomatically.

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media:

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.  
Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

#### Unsuitable extinguishing media:

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 11.13.2019

Page 4 of 13

Revision date: 04.06.2020

## Ceramic Finish Clear Coat

Do not use water jet.

### Specific hazards during fire-fighting:

Flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Thermal decomposition may produce irritating/toxic fumes/gases.

### Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

### Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

### Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

### Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

### Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

## SECTION 7: Handling and storage

### Precautions for safe handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 11.13.2019

Page 5 of 13

**Revision date:** 04.06.2020

### Ceramic Finish Clear Coat

areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

**Conditions for safe storage, including any incompatibilities:**

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

**Occupational Exposure limit values:**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 25 ppm
	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 240 mg/m <sup>3</sup>
	Propan-2-ol	67-63-0	PEL: 400 ppm (OSHA PEL TWA 980 mg/m <sup>3</sup> )
NIOSH	2-Butoxyethanol	111-76-2	IDLH: 700 ppm
	2-Butoxyethanol	111-76-2	TWA: 5 ppm (REL (for up to a 10 hour work day))
	2-Butoxyethanol	111-76-2	TWA: 24 mg/m <sup>3</sup> (REL (for up to a 10 hour work day))
	Propan-2-ol	67-63-0	IDLH: 2000 ppm
	Propan-2-ol	67-63-0	STEL: 500 ppm (1,225 mg/m <sup>3</sup> )
	Propan-2-ol	67-63-0	TWA: 400 ppm (980 mg/m <sup>3</sup> )
ACGIH	2-Butoxyethanol	111-76-2	8-Hour TWA: 20 ppm
	Propan-2-ol	67-63-0	STEL: 400 ppm
	Propan-2-ol	67-63-0	TWA: 200 ppm
United States(California)	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 20 ppm (OSHA (California))
	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 97 mg/m <sup>3</sup> (OSHA (California))
	Propan-2-ol	67-63-0	PEL: 980 mg/m <sup>3</sup> (400 ppm)
	Propan-2-ol	67-63-0	STEL: 1225 mg/m <sup>3</sup> (500 ppm)

**Biological limit values:**

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	2-Butoxyethanol	111-76-2	Butoxyacetic acid (BAA) in urine (with hydrolysis) - (creatinine)	Creatinine in Urine	End of shift	200 mg/g

**Information on monitoring procedures:**

Not determined or not applicable.

**Appropriate engineering controls:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 11.13.2019

Page 6 of 13

Revision date: 04.06.2020

## Ceramic Finish Clear Coat

Effective ventilation in all processing areas.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or safety glasses with side shields

#### Skin and body protection:

Chemical resistant clothing, chemical resistant gloves

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory protection

### General hygienic measures:

Handle in accordance with good industrial hygiene and safety measures. Wash hands and face after handling chemical products. Wash hands before eating, drinking and smoking. Wash hands at the end of the workday. Appropriate techniques should be applied to remove contaminated clothing and shoes. Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Liquid
Odor	Std.
Odor threshold	Not determined or not available.
pH	6
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Not determined or not available.
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

### Other information

## SECTION 10: Stability and reactivity

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 11.13.2019

Page 7 of 13

Revision date: 04.06.2020

## Ceramic Finish Clear Coat

### Reactivity:

Stable and non-reactive under normal conditions of use, storage and transport.

### Chemical stability:

Stable under normal storage and handling conditions.

### Possibility of hazardous reactions:

Under normal conditions of storage and use, hazardous reactions will not occur.

### Conditions to avoid:

Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.

### Incompatible materials:

Strong oxidizing agents and strong acids.

### Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Route	Result
Distillates (petroleum), straight-run middle	inhalation	LC50 Rat: >2.53 mg/L (4 Hours)
2-Butoxyethanol	oral	LD50 Rat: 470 mg/kg
	dermal	LD50 Rabbit: 220 mg/kg
	inhalation	LC50 Rat: 450 ppmV (4H)
Propan-2-ol	oral	LD50 Rabbit: 6410 mg/kg
	dermal	LD50 Rabbit: 12,800 mg/kg
	inhalation	LD50 Rabbit: 72.6 mg/L (4 H)

### Skin corrosion/irritation

#### Assessment:

Causes skin irritation.

#### Product data:

No data available.

#### Substance data:

Name	Result
2-Butoxyethanol	Causes skin irritation
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	Causes severe burns and serious eye damage.
Alcohols, C12-14-secondary, ethoxylated	Causes skin irritation.

### Serious eye damage/irritation

#### Assessment:

Causes serious eye damage.

#### Product data:

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 11.13.2019

Page 8 of 13

Revision date: 04.06.2020

## Ceramic Finish Clear Coat

No data available.

### Substance data:

Name	Result
2-Butoxyethanol	Causes serious eye irritation
Propan-2-ol	Causes serious eye irritation.
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	Causes serious eye damage.
Alcohols, C12-14-secondary, ethoxylated	Causes serious eye damage.

### Respiratory or skin sensitization

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Carcinogenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

#### International Agency for Research on Cancer (IARC):

Name	Classification
2-Butoxyethanol	Group 3
Propan-2-ol	Group 3

#### National Toxicology Program (NTP):

Name	Classification
Propan-2-ol	Not Applicable

**OSHA Carcinogens:** Not applicable

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Reproductive toxicity

#### Assessment:

Suspected of damaging fertility or the unborn child.

#### Product data:

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

#### Assessment:

May cause drowsiness or dizziness.

#### Product data:

No data available.



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 11.13.2019

Page 9 of 13

Revision date: 04.06.2020

## Ceramic Finish Clear Coat

### Substance data:

Name	Result
Propan-2-ol	May cause drowsiness or dizziness.

### Specific target organ toxicity (repeated exposure)

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

#### Substance data:

Name	Result
Distillates (petroleum), straight-run middle	May cause damage to spleen, liver, and bone marrow through prolonged or repeated exposure.

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

#### Substance data:

Name	Result
Distillates (petroleum), straight-run middle	May be fatal if swallowed and enters airways.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Result
2-Butoxyethanol	EC50 Daphnia magna (Water flea): 1,550 mg/L (48 h)

### Chronic (long-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Result
2-Butoxyethanol	NOEC Brachydanio rerio: 100 mg/L (21 Days)

### Persistence and degradability

**Product data:** No data available.

#### Substance data:

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 11.13.2019

Page 10 of 13

Revision date: 04.06.2020

## Ceramic Finish Clear Coat

Name	Result
Distillates (petroleum), straight-run middle	Readily biodegradable.
2-Butoxyethanol	Readily biodegradable.
Propan-2-ol	Readily biodegradable in water.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

### Results of PBT and vPvB assessment

#### Product data:

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT..

**vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB..

#### Substance data:

##### PBT assessment:

Distillates (petroleum), straight-run middle	Substance is not PBT.
2-Butoxyethanol	This substance is not PBT.
Propan-2-ol	This substance is not PBT.

##### vPvB assessment:

Distillates (petroleum), straight-run middle	Substance is not vPvB.
2-Butoxyethanol	This substance is not vPvB.
Propan-2-ol	This substance is not vPvB.

**Other adverse effects:** No data available.

## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to characterize all waste material according to regulatory entities.

### Contaminated packages:

Not determined or not applicable.

## SECTION 14: Transport information

### United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not Regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 11.13.2019

Page 11 of 13

Revision date: 04.06.2020

## Ceramic Finish Clear Coat

### International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

## SECTION 15: Regulatory information

### United States regulations

#### Inventory listing (TSCA):

64741-44-2	Distillates (petroleum), straight-run middle	Listed
111-76-2	2-Butoxyethanol	Listed
67-63-0	Propan-2-ol	Listed
61789-77-3	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	Listed
84133-50-6	Alcohols, C12-14-secondary, ethoxylated	Listed

**Significant New Use Rule (TSCA Section 5):** None of the ingredients are listed.

**Export notification under TSCA Section 12(b):** None of the ingredients are listed.

**SARA Section 302 extremely hazardous substances:** None of the ingredients are listed.

#### SARA Section 313 toxic chemicals:

64741-44-2	Distillates (petroleum), straight-run middle	Not Listed
111-76-2	2-Butoxyethanol	Not Listed
67-63-0	Propan-2-ol	Listed
61789-77-3	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	Not Listed
84133-50-6	Alcohols, C12-14-secondary, ethoxylated	Not Listed

**CERCLA:** None of the ingredients are listed.

**RCRA:** None of the ingredients are listed.

**Section 112(r) of the Clean Air Act (CAA):** None of the ingredients are listed.

**Massachusetts Right to Know:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 11.13.2019

Page 12 of 13

Revision date: 04.06.2020

## Ceramic Finish Clear Coat

64741-44-2	Distillates (petroleum), straight-run middle	Not Listed
111-76-2	2-Butoxyethanol	Listed
67-63-0	Propan-2-ol	Listed
61789-77-3	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	Not Listed
84133-50-6	Alcohols, C12-14-secondary, ethoxylated	Not Listed

### New Jersey Right to Know:

64741-44-2	Distillates (petroleum), straight-run middle	Not Listed
111-76-2	2-Butoxyethanol	Listed
67-63-0	Propan-2-ol	Listed
61789-77-3	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	Not Listed
84133-50-6	Alcohols, C12-14-secondary, ethoxylated	Not Listed

### New York Right to Know:

64741-44-2	Distillates (petroleum), straight-run middle	Listed
111-76-2	2-Butoxyethanol	Listed
67-63-0	Propan-2-ol	Listed
61789-77-3	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	Not Listed
84133-50-6	Alcohols, C12-14-secondary, ethoxylated	Not Listed

### Pennsylvania Right to Know:

64741-44-2	Distillates (petroleum), straight-run middle	Not Listed
111-76-2	2-Butoxyethanol	Listed
67-63-0	Propan-2-ol	Listed
61789-77-3	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	Not Listed
84133-50-6	Alcohols, C12-14-secondary, ethoxylated	Not Listed

**California Proposition 65:** None of the ingredients are listed.

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

### Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 11.13.2019

Page 13 of 13

**Revision date:** 04.06.2020

**Ceramic Finish Clear Coat**

**NFPA:** 0-0-0

**HMIS:** 0-0-0

**Initial preparation date:** 11.13.2019

**Revision date:** 04.06.2020

**End of Safety Data Sheet**