



The Armor All/STP Products Company

1221 Broadway
Oakland, CA 94612
Tel. (510) 271-7000

Material Safety Data Sheet

I Product: STP® POWER STEERING FLUID WITH STOP LEAK		
Description: LIGHT RED LIQUID WITH A HYDROCARBON ODOR		
Other Designations	Distributor	Emergency Telephone Nos.
Power Steering Lubricant with stop leak	The Armor All/STP Products Company 1221 Broadway Oakland, CA 94612	For Medical emergencies call: (800) 446-1014 For Transportation Emergencies call: (800) 424-9300 (Chemtrec)

II Health Hazard Data	III Hazardous Ingredients						
<p>May cause mild eye irritation. Prolonged skin contact may cause irritation, defatting of the skin or dermatitis. Vapors or mists may cause respiratory irritation, headache, dizziness or drowsiness. Swallowing may cause irritation, nausea, vomiting and diarrhea. Aspiration from ingestion may cause lipid pneumonia. Individuals with preexisting skin disorders may be at increased risk from exposure to this product. Under normal consumer use and conditions, the likelihood of adverse health effects is low.</p> <p>FIRST AID: EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. If irritation persists, get medical attention. SKIN CONTACT: Remove contaminated clothing. Wash contact area with soap and water. If irritation persists, get medical attention. INGESTION: Do not induce vomiting. Get medical attention by calling Poison Control or a doctor. If vomiting occurs, keep head below hips to prevent aspiration. INHALATION: If symptoms develop, remove to fresh air. If breathing becomes difficult, give oxygen or administer artificial respiration. Get medical attention.</p>	<table border="1"> <thead> <tr> <th>Ingredients</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>Petroleum Distillates CAS# 64742-54-7 64742-65-0</td> <td>90-100%</td> <td>5 mg/ m³ - TWA PEL/TLV TWA</td> </tr> </tbody> </table> <p>TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average. PEL = Permissible Exposure Limit</p> <p>None of the ingredients in this product are on the IARC, NTP or OSHA carcinogen list.</p> <p>Petroleum Distillates: Oral Rat LD50 >5 g/kg; LD50 Skin rabbit: >5 g/kg</p>	Ingredients	Concentration	Worker Exposure Limit	Petroleum Distillates CAS# 64742-54-7 64742-65-0	90-100%	5 mg/ m ³ - TWA PEL/TLV TWA
Ingredients	Concentration	Worker Exposure Limit					
Petroleum Distillates CAS# 64742-54-7 64742-65-0	90-100%	5 mg/ m ³ - TWA PEL/TLV TWA					

IV Special Protection and Precautions	V Transportation and Regulatory Data
<p>Hygienic Practices: Wash hands thoroughly after contact. Do not handle or store at temperatures greater than 100°F.</p> <p>Engineering Controls: Use local and/or general ventilation to minimize exposure to vapor or mists.</p> <p>Personal Protective Equipment: Wear safety glasses or splash-proof goggles. Wear neoprene or nitrile gloves to prevent skin contact. Use a NIOSH-approved respirator if exposure exceeds occupational limits. Keep container closed when not in use. KEEP OUT OF REACH OF CHILDREN</p>	<p>DOT/IMO/IATA: Not Restricted. TSCA Status: All ingredients in this product are listed on the TSCA inventory. EPA - SARA Title III/CERCLA: This product is regulated under Sections 311/312. This product contains no chemicals, which are regulated under Section 313 and Section 304/CERCLA.</p>

VI Spill Procedures/Waste Disposal	VII Reactivity Data
<p>Spill Procedures: Wear personal protective equipment. Collect with suitable absorbent material and place into a container for disposal. Report spills and releases as required. For spills of multiple products, responders should evaluate the MSDS's of the products for incompatibility with this product.</p> <p>Waste Disposal: Dispose of in accordance with all applicable federal, state and local regulations.</p>	<p>Stability: Stable Hazardous Polymerization: Will not occur. Hazardous Decomposition: Carbon monoxide, carbon dioxide and reactive hydrocarbons. Incompatibilities: Strong oxidizing agents. Keep away from excessive heat and open flames.</p>

VIII Fire and Explosion Data	IX Physical Data
<p>Flash Point: 300°F (COC) Fire Extinguishing Agents: Foam, carbon dioxide, dry chemical or water fog. Cool fire exposed containers with water. Products of Combustion: Carbon monoxide, carbon dioxide and reactive hydrocarbons.</p>	<p>Boiling Point.....>620°F Specific Gravity 0.88 Solubility in Water.....Negligible</p>