



Warning

Hazard statements:

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

Precautionary statements:

Avoid breathing mist/vapours/spray. Wear protective gloves/protective clothing/eye protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off contaminated clothing and wash before reuse. IF exposed or concerned: Get medical advice/attention. IF ON SKIN: Wash with plenty of water.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Product contains:

(R)-p-mentha-1,8-diene

First aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately rinse with water. If skin irritation or rash occurs: Get medical advice/attention.

After eye contact: Protect unharmed eye. Remove contact lenses if worn, if possible. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately.

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.

Firefighting measures

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit.

Additional information No further relevant information available

SHORE
CORPORATION



901
Drying Agent

High performance drying agent with UV Protectant. Aids in repelling water off windshields during wet weather driving.

Directions:

Dilution rates range from 128 to 300 : 1 with water or consult your representative for specific dilution instructions.

Storage Instructions:

Product may become unstable if cooled below 50°F. Keep product warm and above bare concrete floors. If product becomes unstable, add hot water and mix well. Product can be used if thawed properly.

NFPA ratings (scale 0 - 4)

HEALTH 2
FIRE 1
REACTIVITY 0

DOT Shipping

Not Regulated

240 - 1 Recommended Ratio Pink Tip 511 Hydrominder™

Shore Corporation 2917 Spruce Way Pittsburgh, PA 15201
(412) 471 - 3330 (412) 471 - 3260 fax
www.shorecorporation.com

CC0901

5/26/2015