



SB 2600 EIFScrub

SB 2600 EIFScrub is a non acid cleaner for the general maintenance and cleaning of EIFS surfaced buildings and most painted trim such as fascia, soffit, gutters and downspouts. SB 2600 will remove atmospheric soiling, auto and diesel exhaust, some oxidation stains and most organic growth. SB 2600 EIFScrub is also recommended for cleaning of conventional stucco, concrete, painted surfaces, and vinyl and aluminum siding.

Preparation

Provide protection for foliage and pedestrian traffic. Test all surfaces which might be exposed to product for possible adverse reactions. Protect all surfaces and surrounding areas from possible damage which might occur from spillage or spray during usage. Concentrated product may damage aluminum surfaces.

All projects should start with a test application to determine the suitability of the cleaner, acceptable application method and dilution ratio. Test areas of at least 10 square feet are recommended and should involve the most severely contaminated condition. When possible, the test area should be left to dry in order to check for any latent reaction that might require a change in methods or dilutions ratio.

Dilution and Coverage

Dilution: 1 to 4 parts water to 1 part product -- test application recommended

Coverage: Dependent upon substrate and other conditions

Application

Protect and/or wet down foliage and nearby surfaces before application of the SB 2600. If it is a hot, dry day, pre-wet the EIFS surface to cool it down. SB 2600 EIFScrub may be applied by low pressure spray, synthetic fiber brush or roller. Brush agitation may be helpful on some projects or areas with the most buildup of soils. Dwell times may vary from 5 to 20 minutes. Longer times will not damage most surfaces as long as it is kept wet by misting with either more product or water. Do not allow the cleaner to dry on the surface. Removal of the cleaner and contamination can be accomplished with pressure rinsing equipment or a garden hose. Care should be taken in the selection of water pressure and the wand tip angle to avoid damage to the EIFS surface. Most manufacturers recommend 600 psi or less with a tip angle of 45 degrees held about a foot from the surface. If using a hose, mild brush agitation may be required to complete remove the loosened soils. In all cases, a thorough rinsing is required. Cleaning efficiency can be improved by the use of warm, not scalding, water pressure rinsing equipment in some projects. Application of the cleaner requires less time per square area than removal. After the dwell time of a section is reached, it is suggested to use a quick, low pressure rinse to remove any unreacted cleaner before the slower process of removing the loosened soils is started.

SB 2600 is for use by professional contractors only. Projects should not be undertaken when temperatures are below 50 degrees F. Do not allow the cleaner to dry on the surface. Misting of drying cleaner is permissible to avoid possible reapplication. Concentrated cleaner may dull bright aluminum and it should not be used near external surface metalized glass or self cleaning glass.

Before/After Using SB 2600 on EIFS Test Panel for Project



Technical Data

Appearance: Amber Liquid	pH: 14 in Concentrate
Biodegradable: Yes	Rinsing: Complete
Flash Point: None	Solubility: 100%
Foaming: High	Stability: Good
Odor: Citric	Wetting Ability: Excellent

Safety

Causes severe skin burns and eye damage. Causes serious eye damage.



WARNING

Refer to product SDS or product label for hazard statements, precautionary statements and safety information



SB 2600 EIFScrub

SB 2600 EIFScrub is a non acid cleaner for the general maintenance and cleaning of EIFS surfaced buildings and most painted trim such as fascia, soffit, gutters and downspouts. SB 2600 will remove atmospheric soiling, auto and diesel exhaust, some oxidation stains and most organic growth. SB 2600 EIFScrub is also recommended for cleaning of conventional stucco, concrete, painted surfaces, and vinyl and aluminum siding.

Warranty

Shore Corporation warrants that this product conforms to the chemical composition described in the Product Label. SHORE CORPORATION EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Shore Corporation shall not be responsible for any direct or consequential damages sustained as a result of the use of this product. Further, Shore Corporation shall not be liable for personal injuries, property damage or any other damages as a result of the use of this product, the sole responsibility of Shore Corporation under the within WARRANTY being the replacement of any nonconforming product. Acceptance and use of this product absolves Shore Corporation from any other such liability whatsoever and from whatever source. The within WARRANTY may not be modified or extended by Shore Corporation representatives or distributors, neither of which are empowered to make any product representation inconsistent with the terms hereof.

Contact

Trained representatives are available to assist with project assistance and product recommendations. Call **412/471-3330**.