

SB 2790 Con-D-Soil

SB 2790 Con-D-Soil is a highly effective non-acidic cleaner for all concrete and many masonry surfaces. SB 2790 can be successful in the removal of light to moderate soiling, biological fouling, most grease and oil deposits, rubber heel marks, some oxidation stains and certain other surface deposits. It is highly effective in cleaning of commercial tile and grout. SB 2790 is recommended for the removal of all form releases and powdered release agents on stamped concrete before sealing. This product should also be used to clean existing slabs before apply a penetrating or film forming treatment or sealer. SB 2790 is an excellent general purpose cleaner and can be used to clean most painted surfaces, vinyl and aluminum siding, decks and vehicles.

Preparation

Provide protection for foliage, pedestrian and vehicle traffic. Test all non-masonry surfaces for possible adverse reactions. Protect all surfaces and situations where damage may result from spillage or material drift.

All projects should start with a test application to determine cleaner suitability, dilution ratio and acceptable method for application. Test areas of at least 10 square feet are recommended and should involve the most severely contaminated area. Final determination of product acceptance should not be made until the test area has become dry.

Dilution and Coverage

Dilution: 1 to 5 parts water to 1 part product -- test application recommended. See Other Product Uses below.

Coverage: Dependent upon substrate and other conditions

Application

SB 2790 Con-D-Soil is most effective when applied by low-pressure spray. Brush application and agitation may prove helpful on some surfaces. Dwell times are from 5 to 30 minutes. Do not let the cleaner dry on surfaces; mist with water or diluted cleaner to keep the surfaces wet. Removal of the cleaner and contaminant can be accomplished most successfully with pressure washing equipment. If only garden hose rinsing is available, light scrubbing or brooming during rinsing may be required. A thorough rinsing is required. Dilutions are 0 to 5 parts water.

SB 2790 Con-D-Soil is for use by professional contractors only. Projects where complete rinsing cannot be accomplished will require an additional neutralization step. Do not use on bright aluminum, metalized glass, "self cleaning" glass or fine wood surfaces.

Other Product Uses / Dilutions

Engine Degreaser

No Scrub Tire/Wheel

Concrete or Brick
Heavy Duty Degreaser

1-2 Parts Water to 1 Part Product
1-3 Parts Water to 1 Part Product
1-5 Parts Water to 1 Part Product
1-10 Parts Water to 1 Part Product

All Purpose Cleaner Cars, Trucks, Trailers Pressure Washers 1-40 Parts Water to 1 Part Product 1-60 Parts Water to 1 Part Product 1-100 Parts Water to 1 Part Product

Before/After Photo of Concrete Floor at Meat Processing Facility in Chicago, IL



Technical Data

Appearance: Clear Liquid pH: 14 in Concentrate
Biodegradable: Yes Rinsing: Complete
Flash Point: None Solubility: 100%
Foaming: High Stability: Good
Odor: Mild Citrus Wetting Ability: Excellent

Safety

Causes severe skin burns and eye damage



DANGER

Refer to product SDS or product label for hazard statements, precautionary statements and safety information



SB 2790 Con-D-Soil

SB 2790 Con-D-Soil is a highly effective non-acidic cleaner for all concrete and many masonry surfaces. SB 2790 can be successful in the removal of light to moderate soiling, biological fouling, most grease and oil deposits, rubber heel marks, some oxidation stains and certain other surface deposits. It is highly effective in cleaning of commercial tile and grout. SB 2790 is recommended for the removal of all form releases and powdered release agents on stamped concrete before sealing. This product should also be used to clean existing slabs before apply a penetrating or film forming treatment or sealer. SB 2790 is an excellent general purpose cleaner and can be used to clean most painted surfaces, vinyl and aluminum siding, decks and vehicles.

Warranty

Shore Corporation warrants that this product conforms to the chemical composition described in the Product Label. SHORE CORPORATION EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Shore Corporation shall not be responsible for any direct or consequential damages sustained as a result of the use of this product. Further, Shore Corporation shall not be liable for personal injuries, property damage or any other damages as a result of the use of this product, the sole responsibility of Shore Corporation under the within WARRANTY being the replacement of any nonconforming product. Acceptance and use of this product absolves Shore Corporation from any other such liability whatsoever and from whatever source. The within WARRANTY may not be modified or extended by Shore Corporation representatives or distributors, neither of which are empowered to make any product representation inconsistent with the terms hereof.

Contact

Trained representatives are available to assist with project assistance and product recommendations. Call **412/471-3330**.