PRODUCTS / Z-020 TORNADOR® BLACK

Z-020 INSTRUCTIONS FOR USE

SAFETY REQUIREMENTS

- · KEEP OUT OF REACH OF CHILDREN.
- The TORNADOR® Black can cause considerable noise from air pressure. Please wear hearing protection
- · When using the TORNADOR® Black, small pieces of debris can be whirled into the air. Always wear protective goggles or glasses to prevent eye damage.
- The TORNADOR® Black nebulizes the cleaning liquid. Wear appropriate respiratory protection to prevent health hazards from inhalation.
- · Use in well ventilated area.
- · Do not exceed 110 psi.
- Do not use with acidic, flammable or combustible products; "USE ONLY WITH TORNADOR PRODUCTS."

- Do not point cleaning tool at face or body.
 Avoid breathing dust or handling debris that can be harmful to your health.
 Should you notice a tool malfunction, discontinue use and contact your supplier.
- Use caution when other people are in your surroundings and work area.
 Always disconnect the devise from the air supply when not in use and before changing accessories or when preforming routine maintenance.
- · Always check the devise for leaking hoses, loose fittings or damaged parts.
- · We recommend that you never clean any safety related components with the TORNADOR® Black tool, i.e., safety belts, electrical or electronic modules.

AIR REQUIREMENTS

The TORNADOR® Black cleaning tool requires a constant air pressure between 5.5 and 6.3 bar 78 to 90 psi, for optimum performance. DO NOT EXCEED 110 psi

CAUTION: Constant air supply rates vary depending on the size and power of the compressor. Always make sure tank and air lines are free from impurites, oil and water contamination.

