

TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

SECTION 1. IDENTIFICATION

Product name : TM ASPEN MINT PRESOAK 5 GA

Product code : TM144-05 TM144-05

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone num-

ber

1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : CAR WASH

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin corrosion : Category 1

Serious eye damage : Category 1

Specific target organ toxicity - repeated exposure (Inhala-

tion)

Category 2 (Respiratory Tract)

GHS label elements

Hazard pictograms :





Signal word : Danger

Hazard statements : Causes severe skin burns and eye damage.

May cause damage to organs (Respiratory Tract) through pro-

longed or repeated exposure if inhaled.

Precautionary statements : Prevention:

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Wear protective gloves/ protective clothing/ eye protection/ face



TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Get medical advice/ attention if you feel unwell. Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Sodium C14-16 olefin sulfonate	68439-57-6	>= 10 - < 20
2-Butoxyethanol	111-76-2	>= 1 - < 5
Sodium hydroxide	1310-73-2	>= 2 - < 3
Sodium Xylene Sulfonate	1300-72-7	>= 1 - < 5
Tetrasodium EDTA	64-02-8	>= 1 - < 5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Take off contaminated clothing and shoes immediately.

If on skin, rinse well with water.

Wash contaminated clothing before re-use. If skin irritation persists, call a physician.



TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If swallowed : Get medical attention immediately.

Do NOT induce vomiting. Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

Causes serious eye damage.

May cause damage to organs through prolonged or repeated

exposure if inhaled. Causes severe burns.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

icts

Carbon oxides
Sulphur oxides

Sodium oxides

Nitrogen oxides (NOx)

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Avoid breathing dust.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.



TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Avoid contact with skin and eyes.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-Butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
Sodium hydroxide	1310-73-2	С	2 mg/m3	ACGIH
		С	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z-1
		С	2 mg/m3	OSHA P0

Hazardous components without workplace control parameters

Components	CAS-No.
Sodium C14-16 olefin sul-	68439-57-6



TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

fonate	
Sodium Xylene Sulfonate	1300-72-7
Tetrasodium EDTA	64-02-8

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra-tion	Basis
2-Butoxyethanol	111-76-2	Butoxyace- tic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g Creatinine	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment suppli-

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles and face shield when there is

potential for exposure of the eyes or face to liquid, vapor or

mist.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing Safety shoes

Remove and wash contaminated clothing before re-use.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not smoke. When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : blue

Odour : mint-like

Odour Threshold : not determined



TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

pH : 13

Melting point/freezing point : 0 °C

Boiling point/boiling range : 100 °C

Flash point : $> 100 \, ^{\circ}\text{C}$

Evaporation rate : not determined

Flammability (solid, gas) : No data available

Self-ignition : not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Vapour pressure : not determined

Relative vapour density : not determined

Density : 1.0413 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

not determined

Decomposition temperature : not determined

Viscosity

Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Hazardous polymerisation does not occur.

Conditions to avoid : No data available

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

Sulphur oxides



TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

Sodium oxides

Hazardous decomposition

products

Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eye contact Skin contact Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Remarks: Causes digestive tract burns.

Acute inhalation toxicity : Acute toxicity estimate: 27.83 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

Sodium C14-16 olefin sulfonate:

Acute oral toxicity : LD50 (Rat): 2,079 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 52 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 6,000 mg/kg

2-Butoxyethanol:

Acute oral toxicity : LD50 (Guinea pig): 1,200 mg/kg

Acute inhalation toxicity : LC50 (Guinea pig): > 633 ppm

Exposure time: 1 h

Test atmosphere: dust/mist

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg

Assessment: The component/mixture is moderately toxic after

single contact with skin.



TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

Sodium hydroxide:

Acute oral toxicity : LDLo (Rabbit): 500 mg/kg

Sodium Xylene Sulfonate:

Acute oral toxicity : LD50 (Rat): > 7,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

Tetrasodium EDTA:

Acute oral toxicity : LD50 (Rat, female): 1,780 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 1 - 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks: Causes severe skin burns and eye damage.

The feeling of irritation or pain may be delayed.

Components:

Sodium C14-16 olefin sulfonate:

Species: Rabbit

Result: Irritating to skin.

2-Butoxyethanol:

Method: Directive 67/548/EEC, Annex V, B.4.

Result: Irritating to skin.

Sodium hydroxide:

Result: Corrosive after 3 minutes or less of exposure

Sodium Xylene Sulfonate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Mild skin irritation

Remarks: Information given is based on data obtained from similar substances.

Tetrasodium EDTA:



TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Components:

Sodium C14-16 olefin sulfonate:

Species: Rabbit

Result: Irreversible effects on the eye

2-Butoxyethanol:

Result: Irritating to eyes.

Method: OECD Test Guideline 405

Sodium hydroxide:

Result: Corrosive

Sodium Xylene Sulfonate:

Species: Rabbit

Result: Irritation to eyes, reversing within 7 days

Method: OECD Test Guideline 405

GLP: yes

Tetrasodium EDTA:

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Sodium C14-16 olefin sulfonate:

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

2-Butoxyethanol:

Species: Guinea pig

Method: OECD Test Guideline 406 Result: Not a skin sensitizer.



TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

Sodium hydroxide:

Exposure routes: Skin contact

Species: Humans Result: negative

Sodium Xylene Sulfonate:

Test Type: Buehler Test Exposure routes: Dermal Species: Guinea pig

Method: OECD Test Guideline 406 Result: Does not cause skin sensitisation.

GLP: yes

Tetrasodium EDTA:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Remarks: Information given is based on data obtained from similar substances.

Germ cell mutagenicity

Not classified based on available information.

Components:

Sodium C14-16 olefin sulfonate:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

2-Butoxyethanol:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Tetrasodium EDTA:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.



TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.

Components:

Tetrasodium EDTA:

Exposure routes: Inhalation
Target Organs: Respiratory Tract

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated

exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.



TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

International Regulations

IATA-DGR

UN/ID No. **UN 1760**

Proper shipping name Corrosive liquid, n.o.s.

(Sodium Hydroxide, TETRASODIUM EDTA)

Class Packing group Ш Labels 8 Packing instruction (cargo 855

aircraft)

Packing instruction 851

(passenger aircraft)

IMDG-Code

UN number UN 1760

CORROSIVE LIQUID, N.O.S. Proper shipping name

(Sodium Hydroxide, TETRASODIUM EDTA)

Class 8 Packing group Ш Labels 8 **EmS Code** F-A, S-B Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number **UN 1760**

Corrosive liquids, n.o.s. Proper shipping name

(Sodium Hydroxide, TETRASODIUM EDTA)

Class 8 Packing group Ш Labels 8 **ERG Code** 154 Marine pollutant no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Sodium hydroxide	1310-73-2	1000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards Skin corrosion or irritation



TRANSMATE™ ASPEN MINT PRE-SOAK

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/14/2020 600000002180 Date of first issue: 01/02/2015

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

2-Butoxyethanol 111-76-2 >= 1 - < 5 %


California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 12/14/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN