MANIFOLD & ROUND BODY VALVES





STAINLESS STEEL MANIFOLD VALVES

303 STAINLESS STEEL BLOCK

DEMA

- Stainless steel valves mounted on a 303 stainless steel manifold block. Common inlet port for chemical supply to all valves on both ends. Metering screw available on $\frac{1}{4}$ " NPT model.
- Buna N Seal Pipe Size: 1/4" NPT 1/8" Orifice CV Flow Factor: 0.27

NON-METERING

DEMA STAINLESS STEEL MANIFOLD VALVES

PRICE	PART #	# STA	COIL/VOLTAGE
\$108.01	SODM2NMSS	2	24
\$108.01	SODM2NMSS120	2	120
\$159.97	SODM3NMSS	3	24
\$207.54	SODM4NMSS	4	24
\$207.54	SODM4NMSS120	4	120
\$261.25	SODM5NMSS	5	24
\$261.25	SODM5NMSS120	5	120

California WARNING PROPOSITION 65

WITH METERING

STAINLESS STEEL MANIFOLD VALVES

PRICE	PART #	# STA	COIL/VOLTAGE
\$126.88	SODM2MSS	2	24
\$126.88	SODM2MSS120	2	120
\$184.92	SODM3MSS	3	24
\$136.50	SODM3MSS120	3	120
\$255.01	SODM4MSS	4	24
\$255.01	SODM4MSS120	4	120
\$300.75	SODM5MSS	5	24
\$300.75	SODM5MSS120	5	120
\$22.71	CUDK/1018B	Penair Kit	

California wassas



BRASS MANIFOLD VALVES

RRASS BLOCK



- Stainless steel valves mounted on a solid brass manifold block. Common inlet
 port for chemical supply to all valves on both ends. Metering screw available on
 ¹/₄" NPT model.
- Buna N Seal Pipe Size: 1/4" NPT 1/8" Orifice CV Flow Factor: 0.27

NON-METERING

DEMA BRASS MANIFOLD VALVES

PRICE	PART #	# STA	COIL/VOLTAGE
\$78.47	SODM2NM	2	24
\$78.47	SODM2NM120	2	120
\$114.08	SODM3NM	3	24
\$114.08	SODM3NM120	3	120
\$150.90	SODM4NM	4	24
\$186.86	SODM5NM	5	24
\$186.84	SODM5NM120	5	120

California WARNING PROPOSITION 65

METERING

DEMA BRASS MANIFOLD VALVES

PRICE	PART #	# STA	COIL/VOLTAGE
\$47.20	SODM1M	1	24
\$47.20	S0DM1M120	1	120
\$87.21	SODM2M	2	24
\$87.21	S0DM2M120	2	120
\$126.06	SODM3M	3	24
\$126.06	SODM3M120	3	120
\$166.56	SODM4M	4	24
\$206.22	SODM5M	5	24
\$206.22	SODM5M120	5	120
\$10.71	SODP419724	24V C	oil
\$32.71	SODK4918B	Repair	KIT I

California WARNING PROPOSITION 65

DEMA VALVES



Available in three, four or five stations, can be combined for additional stations
 CV Flow Factor: 2.0 • 15.5 GPM at 60PSI • Viton Diaphragms
 • ½" NPT Inlet



California wasness



NON-METERING STAINLESS STEEL SINGLE STATION ROUND BODY VALVE DEMA VALVES

Buna N Seal
 CV Flow Factor: 0.27
 Max Pressure: 150 PSI
 Min Pressure: 0 PSI

PRICE	PART#	COIL/VOLTAGE	PIPE SIZE	ORIFICE
\$39.72	S0D492S24	Spade 24 vac	1∕₄" NPT	1/8"
California WANNE PROPOSITION 65				

CALIFORNIA PROPOSITION 65 NOTE: some items on this page may fall under the Proposition 65 act. Please consult the State of California Proposition 65 list (oehha.ca.gov/proposition-65/proposition-65-list) to learn more and to see a comprehensive list of Proposition 65 chemicals.



• 3/8" NPT Outlets

DIAPHRAGM VALVES



NORMALLY CLOSED MINI DIAPHRAGM VALVES

DEMA STAINLESS STEEL DIAPHRAGM VALVES

- · 303 investment cast stainless steel body
- Molded water-resistant coil with spade connections
- EPDM diaphragm15.5 GPM flow at 60 PSI
- Bracket and cover included12.6 GPM flow at 40 PSI
- includedAvailable in 24V or 120 V8.9 GPM flow at 20 PSI

VALVE W/O COVER & BRACKET					
\$59.79	S0D463SS24	3/8" NPT			
\$59.79	S0D464SS24	½" NPT			

VALVE W/ COVER & BRACKET					
\$63.03 SOD463SS24C 3/8" NPT					
\$63.03	S0D464SS24C	½" NPT			





NORMALLY CLOSED DIAPHRAGM VALVES

DEMA STAINLESS STEEL DIAPHRAGM VALVES

• 3/4" NPT. 3/4" Orifice • 39 GPM @ 60 PSI

303 investment cast stainless steel body

\$183.23	S0D476SS24	24V
\$183.23	SOD476SS120	120V

California wanno





NORMALLY OPEN MINI DIAPHRAGM VALVES

DEMA VALVES



DEMA

DEMA

PRICE	PART #	PIPE SIZE	VOLT	BODY	MAX PSI	ORIFICE
\$75.03	S0D0442P24	1/4"	24	Brass		1/4"
\$75.03	S0D0442P120	1/4"	120	Brass		1/4"
\$91.57	S0D0463PS24	3/8"	24	Stainless	125	3/8"
\$91.57	S0D0463PS120	3/8"	120	Stainless	123	3/8"
\$91.57	S0D0464PS24	1/2"	24	Stainless		1/2"
\$91.57	S0D0464PS120	1/2"	120	Stainless		1/2"

California WARMING PROPOSITION 65



SOLENOID REPLACEMENT COILS

DEMA VALVES



PRICE	PART #	VOLT	COIL
\$21.63	SODP419124	24V	Series 1 Coil
\$21.63	SODP4191120	120V	Selles I Coll
\$25.23	SODP419224	24V	Carias O Cail
\$25.23	SODP4192120	120V	Series 2 Coil
			•

California WARMIN

WANT TO LEARN MORE ABOUT SOLENOID REPAIR?

From controlling the release of products based on a selected function in your bay to weep system management, solenoid valves play a critical role in nearly all types of car wash equipment. Knowing how to repair and service them is critical to keeping your wash running efficiently.

TO WATCH A SOLENOID SERVICE VIDEO VISIT OUR WEBSITE, OR SIMPLY SCAN THIS QR CODE WITH YOUR HANDHELD MOBILE DEVICE:



SOLENOID VALVES

DEMA SOLENOID VALVES

*Specify voltage (24 or 120)

DEMA

• 90° valve, high flow

• Pressure 150 PSI

Nylon Valve Body

PRICE	PART#	DEMA MODEL #	PIPE SIZE	ORIFICE
\$99.47	S0D466P	466P	3/4"	.750"

California WARNING



SOLENOID VALVES -BUNA-N DIAPHRAGM STANDARD

DEMA SOLENOID VALVES

*Specify voltage (24, 120 or 230)

DEMA

Pressure 150 PSI

- Buna-N Diaphragm Standard
- Valve Body Brass
- Teflon is available

PRICE	PART#	DEMA MODEL #	PIPE SIZE	ORIFICE	REPAIR KIT #
\$77.46	S0D473P	473P	3/8"	.562"	SODK4147
\$77.46	SOD474P	474P	1/2"	.562"	SODK4147
\$83.87	S0D476P	476P	3/4"	.750"	SODK4149

California WARRING PROPOSITION 65



SOLENOID VALVES - NORMALLY CLOSED DIRECT ACTING DIAPHRAGM

DEMA SOLENOID VALVES

*Specify voltage (24 or 120)

DEMA

- Orifice .172"
- Direct Acting Diaphragm
- PVC Valve BodyUsed on Vac Lines with Corrosive Liquid
- Adjustable

PRICE	PART#	DEMA MODEL#	PIPE SIZE	ORIFICE
\$74.98	S0D481P	481P	1/8"	.172"
\$78.68	S0D482P	482P	1/4"	.172"

California WARMING PROPOSITION 65



BRASS NORMALLY OPEN DIAPHRAGM STYLE

DEMA SOLENOID VALVES

*Specify voltage (24 or 120)

DEMA

PRICE	PART#	DEMA MODEL #	PIPE SIZE	ORIFICE
\$108.76	S0D0473P	0473P	3/8"	9/16"
\$108.76	S0D0474P	0474P	1/2"	9/16"
\$115.03	S0D0476P	0476P	3/4"	3/4"

California WARMING PROPOSITION 65



NORMALLY OPEN PLUNGER STYLE

DEMA SOLENOID VALVES

*Specify voltage (24 or 120)

DEMA

PRICE	PART#	DEMA MODEL #	PIPE SIZE	TYPE	PSI
\$86.98	S0D0742P	0742	1/4"		150
\$88.97	S0D0412P	0412	3/8"	Brass	150
\$118.55	S0D0453P	0453	3/8"		1200

California WARNING PROPOSITION 65

SOLENOID VALVES

DEMA SOLENOID VALVES

*Specify voltage (24 or 120)

DEMA

Pressure 150 PSI

· Brass Valve Body

PRICE	PART#	DEMA MODEL#	PIPE SIZE	ORIFICE	DESCRIPTION (NORMALLY CLOSED TYPE)	REPAIR KIT#	
\$45.64	SOD401P	401P	1/4"	.109"	Direct Acting: Buna-n, Teflon, or Viton Seal	SODK4124	
\$60.79	S0D412P	412P	3/8"	.281"		SODK4126	
\$67.65	S0D413P	413P	3/8"	.312"		SODK4127	
\$74.10	S0D414P	414P	1/2"	.438"	Pilot Operated Piston	SODK4128	
\$100.80	SOD416P	416P	3/4"	.593"		SODK4129	
\$133.74	S0D418P	418P	1"	.760"		SODK4130	
\$8.39	SODK4124	Repair Kit (401P)					
\$12.75	SODK4126		Repair Kit (412P)				

California WARMAN





SOLENOID VALVES

DEMA SOLENOID VALVES

*Specify voltage (24 or 120)

DEMA

• Pressure 125 PSI

· Brass Valve Body

PRICE	PART#	DEMA MODEL #	PIPE SIZE	ORIFICE	DESCRIPTION (NORMALLY CLOSED TYPE)
\$49.73	S0D424SS	424P-2	1/4"	.125"	Direct Acting Corrosion Resistant, Available in Teflon or Viton
\$9.25	SODK4124V	41.24	Repair Kit		

California WARMING PROPOSITION 65



SOLENOID VALVES

DEMA SOLENOID VALVES

*Specify voltage (12, 24 or 120)

DEMA

• Pressure 125 PSI

• Diaphragm Type

Built-in Strainer

PRICE	PART#	DEMA MODEL#	PIPE SIZE	ORIFICE	DESCRIPTION (NORMALLY CLOSED TYPE)
\$33.74	S0D442P	442P	1/4"	.250"	Diaphragm Type, Built-in Strainer
\$33.74	SOD443P	443P	3/8"	.250"	Diaphragm Type, Built-in Strainer

California WARMING PROPOSITION 65



SOLENOID VALVES

DEMA SOLENOID VALVES

*Specify voltage (12, 24 or 120)

DEMA

Pressure 1200 PSI

· Brass Valve Body

PRICE	PART#	DEMA MODEL#	PIPE SIZE	ORIFICE	DESCRIPTION (NORMALLY CLOSED TYPE)	REPAIR KIT #
\$85.31	SOD453P	453P	3/8"	.350"	Pilot Operated Piston, High Pressure	SODK4131
\$94.67	S0D453SS	453S	3/8"	.350"	Pilot Operated Piston, High Pressure Stainless Steel Sleeve	SODK4131
\$128.54	SOD454P	454P	1/2"	.500"	Pilot Operated Piston, High Pressure	SODK4132
\$219.15	SOD458P	458P	1"	.937"	Pilot Operated Piston, High Pressure	SODK41332
\$236.78	SOD458PS	458PS	1"	.937"	Pilot Operated Piston, High Pressure Stainless Steel Sleeve	SODK4133
California WARNING PROPOSITION 65						

SOLENOID VALVES & MANIFOLD KITS

MANIFOLD BLOCKS

GC VALVES





- . Brass Body with Viton Seals
- 24V
- 1/4" FPT Port

· Stainless Steel Orifice

. Blocks can be ordered with or without metering screw

•	Max Pressure: 200 PSI
•	Max Temp.: 230°F

- Orifice 3/32"
- · Common inlet port for all valves

PRICE	PART #	METERING	OUTLETS
\$106.87	GC92	NONE	2
\$135.08	GC92M	YES	2
\$159.29	GC93	NONE	3
\$202.60	GC93M	YES	3
\$235.37	GC94	NONE	4

PRICE	PART #	METERING	OUTLETS
\$278.66	GC94M	YES	4
\$252.18	GC95	NONE	5
\$320.59	GC95M	YES	5
\$302.60	GC96	NONE	6
\$405.71	GC96M	YES	6



MANIFOLD BLOCKS

STAINLESS STEEL BODY / VITON SEALS

- · Stainless steel body with Viton seals • Max Temp.: 230°F · Common inlet port for all valves
- Max Pressure: 200 PSI
- Orifice: 3/32" • 24V
- 1/4 FPT Port
- Blocks can be ordered with or without metering screw

• Brass / Nitrile

Choose 24 or 120V*

PORT

PRICE	PART #	METERING	OUTLETS
\$115.64	GCS92	NONE	2
\$146.36	GCS92M	YES	2
\$173.44	GCS93	NONE	3
\$212.14	GCS93M	YES	3
\$241.18	GCS94	NONE	4

PRICE	PART #	METERING	OUTLETS
\$292.70	GCS94M	YES	4
\$289.11	GCS95	NONE	5
\$365.86	GCS95M	YES	5
\$347.32	GCS96	NONE	6
\$439.05	GCS96M	YES	6



MANIFOLD KITS

G.C. VALVES



PRICE	PART #	MANIFOLD KITS
\$19.27	GCCM24	Coil for Manifold Blocks; 24V
\$17.04	GCK115	Plunger Only for Manifold Blocks
\$36.78	GCK21	Repair Kit, Manifold Blocks
\$54.01	GCK41	Repair Kit, Manifold Black Style
\$54.16	GCK621126	C6 Operator Kit Used on "Fragrance" line of car wash manifolds - D0ES NOTINCLUDE Coil, top washer or top nut. INCLUDES : Tube, static seal o-ring, plunger with Kalrez seals and spring.



SOLENOID VALVES

SOLENOID VALVES BRASS / NITRILE SEALS

• Max Pressure: 150 PSI

• Max Temperature: 180°F

GC VALVES



· Stainless Steel

PRICE	PART #	PIPE	ORIFICE	PSI	VOLTAGE
\$116.93	GC140	1/4"	3/8"	1200	24
\$116.93	GC280	3/8"	3/8"		24
\$132.80	GC340	1/2"	3/8"	2200	24
\$117.71	GC281	3/8"	3/8"		120
\$132.80	GC341	1/2"	1/2"		120



SOLENOID VALVES W/ VITON SEALS

GC VALVES



- · Brass or stainless steel body
- Max Pressure: 200 PSI
- · Viton seals
- Orifice: 3/32'

Max Temperature: 230°F	 Choose 24 or 120V

PRICE	PART #	BODY	PORT	METERING
\$29.07	GC091	Brass	1/8"	None
\$39.63	GC091SS	SS		None
\$47.79	GC095	SS		Yes
\$41.00	GC191	Brass	1/4"	None
\$68.75	GC191SS	SS		None
\$55.78	GC195	SS		Yes



*Add -120 to Part # for 120V

LASERWASH G5 KIT

GC VALVES

GC VALVES

PRICE

\$73.21

\$89.39



• High performance, high flow • Kit for Laserwash G5

PART #

GC391 GC491

GC591

\$201.77 GCK900



SOLENOID VALVE KITS FOR C9 VALVES

GC VALVES



\$19.27	GCCM24	24V Coil
\$19.30	GCCM120	120V Coil
\$54.01	GCK41	Kit for 1/8" or 1/4"
\$42.06	GCK391	Kit for ½"
\$41.23	GCK491	Kit for 3/4"
\$50.05	GCK591	Kit for 1"



DIN CONNECTORS FOR C9 COILS GC VALVES



. DIN connectors are available with cords up to 6'

\$6.66	GCP6010	Din Connector
\$6.40	GCP6010-AC	With LED
\$29.40	GCP6010-6	With 6' Cord
\$16.23	GCP6010-12L	½" Conduit with 36" Leads




MANIFOLD BLOCKS & SOLENOID VALVES

MANIFOLD BLOCKS

IMI NORGREN KIP FLUID CONTROL VALVE SERIES





- · Common inlet port for all valves
- Blocks can be ordered with or without metering screw

PRICE	PART #	PORT	VOLT.	METERING	OUTLETS
\$85.12	SK2X910V2				2
\$112.58	SK2X910V3				3
\$143.00	SK2X910V4			NONE	4
\$170.57	SK2X910V5				5
\$193.69	SK2X910V6	1⁄4" NPTF	24		6
\$98.67	SK2X911VM2	/4" NPIF	24		2
\$134.29	SK2X911VM3				3
\$169.91	SK2X911VM4			YES	4
\$212.35	SK2X911VM5				5
\$236.49	SK2X911VM6				6



SOLENOID VALVES

G.C. VALVES





PRICE	PART #	PORT	ORIFICE	VOLTAGE	PSI	GC MODEL #
\$59.11	GC100	1/4"	5/32"	120	150	S311AF02N3BD7
\$60.44	GC105	1/4"	5/32"	120	150	S311AF02V3BD7
\$59.11	GC110	1/4"	5/32"		150	S311AF01N3BD7
\$101.69	GC130	1/4"	3/32"	24	150	S306AF01V3BC9
\$90.18	GC210	3/8"	5/8"	24	0-140	S201AF01N5CG4
\$85.82	GC305	1/2"	5/8"		150	S211SF01N5DG4
\$92.89	GC300	1/2"	5/8"	120	150	S211SF02N5DG4
\$86.71	GC315	1/2"	5/8"		200	S211UF01N5DG4
\$127.27	GC0824B	1/2"	1/2"		250	S211AF01K4DG1
\$85.82	GC235	3/8"	5/8"	24	250	S211YF01N5CG4
\$86.57	GC205	3/8"	5/8"		5-200	S211SF01N5CG4
\$90.18	GC0824NC	1/2"	5/8"		150	S201SF01N5DG4
\$86.72	GC200	3/8"	3/8"		150	S211SF02N5CG4
\$90.68	GC211	3/8"	5/8"		0-140	S201AF02N5CG4
\$105.94	GC405	3/4"	3/4"		140	S201AF02N5EG5
\$152.23	GC500	1"	1"	120	0-100	S201F02N5FC9
\$85.82	GC213	3/8"	5/8"		4-200	S211AF02N5CG4
\$86.57	GC348	1/2"	5/8"		4-200	S211AF02N5DGF
\$66.49	GC030	1/8"	1/8"		260	S301AF02N8ADS



NORMALLY CLOSED STAINLESS STEEL & **BRASS SOLENOID VALVE**

G.C. VALVES

- 24 VAC
- 1" NPT
- Solenoid w/ Buna Seals

\$612.75 GC512



SOLENOID VALVES

NORMALLY OPEN, BRASS BODY, PILOTED DIAPHRAGM



PRICE	PART #	PORT	VOLT.	PSI	GC MODEL #
\$122.29	GC220	3/8"	24		S212SF01N5CG4
\$180.77	GC215	3/8"	120	150	S212SF02N5CG4
\$122.29	GC325	1/2"	24	130	S212SF01N5DG4
\$122.29	GC320	1/2"	120		S212SF02N5DG4
•					



NORMALLY CLOSED SOLENOID VALVE

G.C. VALVES

- 120 VAC
- · Viton Seal
- Direct Acting

\$71.12

GC112



SOLENOID VALVES

G.C. VALVES STAINLESS STEEL



PRICE	PART #	PIPE	ORIFICE	VOLTAGE	PSI
\$52.96	GCS0224	1/8"	1/8"	24	0-155
\$69.47	GCS0424	1/4"	5/32"	24	0-150
\$210.56	GC350	1/2"	5/8"	24	4-200
\$210.56	GC355	1/2"	5/8"	120	4-200
\$249.92	GC270	3/8"	5/8"	24	4-200
\$210.56	GC275	3/8"	5/8"	120	4-200
\$215.45	GC450	3/4"	3/4"	24	4-200
\$215.45	GC455	3/4"	3/4"	120	4-200
\$596.36	GC506	1"	1"	120	5-150



SOLENOID VALVES



IMI NORGREN KIP SERIES 3 FLUID CONTROL VALVE SERIES

- · 24V 2-way normally closed
- · Ideal for liquid, air, or vacuum applicationsk
- Max operating pressure 150 PSI
- Operating temperature: -4 to 104°F
- Buna seal
- · Coil: dry tape wrapped with leads
- Stainless Steel

PRICE	PART #	PORT	CONNECTOR	ORIFICE		
\$48.16	SKP351015	1⁄4" NPTF	1⁄4" NPT	1/8"		
\$27.15	SK0242	Conduit Housing				
\$21.13	SKP351015-K	Repair Parts Kit				

SOLENOID VALVE REPAIR KITS

IMI NORGREN KIP FLUID CONTROL VALVE SERIES





STANDARD VALVE WITH FLYING

SIDE METERING

NORMALLY OPEN

NON-METERING

NORGREN

BOTTOM METERING

SOLENOID VALVES

IMI NORGREN KIP FLUID CONTROL VALVE SERIES



NORGREN

NORGREN

NORGREN

• For soap, wax, tire cleaner, or presoak

- 24V 2-way normally closed
- Max operating pressure 150 PSI
 Available in ¼" or ½" FPT
- Viton seals used for long life
 - · Spade terminals for easy wiring
- · Stainless Steel

PRICE	PART #	PORT	VOLTAGE	METERING	ORIFICE
\$36.12	SKM02B	1/8" NPTF		BOTTOM	3/32
\$39.08	SKM02S	1/8" NPTF		SIDE	3/32
\$38.55	SKM04S	1⁄4" NPTF	24	SIDE	1/8
\$30.28	SKNM02	1/8" NPTF	24	NONE	3/32
\$33.28	SKNM04	1⁄4" NPTF		NONE	1/8
\$41.11	SKN004	1/4" NPTF		NORMALL	Y OPEN



V61/V62 SERIES - 3/2NC - NON-LOCKING


NON-LOCKING SOLENOIDS





V61/V62 SERIES - 5/2 - NON-LOCKING

NON-LOCKING SOLENOIDS





V61/V62 SERIES - 5/2 - NON-LOCKING

NON-LOCKING SOLENOIDS

PRICE	KR#	MFG #	DESCRIPTION	ACTUATION	PORT (NPT)	FLOW CV (I/MIN)	OPERATING PRESSURE
\$117.40	SK0410-120	V61R511A-A318JB	1/4" • 110/120VAC		1/4"	1.30 (1300)	
\$117.40	SK0410-24DC	V61R511A-A313JB	1/4 - 24//DC	Solenoid/Solenoid	1/4"	1.30 (1300)	44 - 145 PSI
\$166.19	SK0610-120	V62S511A-A318JB	3/8" 10/120VAC	Solellola/Solellola	3/8"	2.60 (2600)	
\$166.19	SK0610-24DC	V62S511A-A313JB	3/8" • 24VDC		3/8"	2.60 (2600)	



V61/V62 SERIES - 5/3 APB - NON-LOCKING

NON-LOCKING SOLENOIDS





PRICE	KR#	MFG #	DESCRIPTION	ACTUATION	PORT (NPT)	FLOW CV (I/MIN)	OPERATING PRESSURE
\$152.87	SK0415-120	V61R611A-A318JB	1/4" • 110/120VAC		1/4"	1.30 (1300)	
\$152.87	SK0415-24DC	V61R611A-A313JB	1/4" • 24VDC	Solenoid/Solenoid	1/4"	1.30 (1300)	44 - 145 PSI
\$201.66	SK0615-120	V62S611A-A318JB	3/8" 110/120VAC	Solellola/Solellola	3/8"	2.60 (2600)	44 - 145 PSI
\$201.66	SK0615-24DC	V62S611A-A313JB	3/8" 24VDC		3/8"	2.60 (2600)	







SOP1202/04/06



SOP1208/12/14





SOP1218

SOLENOID VALVES

• 18" lead wires

PARKER

· Conduit coil

NPT Pipe

PRICE	PART #	PIPE	VOLTAGE	PSI	BODY	DESCRIPTION
\$186.77	S0P1200	1"	120/60	150		Normally Closed
\$193.93	SOP1202-120	1/2"	120/60	150]	Normally Open
\$187.30	S0P1202	1/2"	24/60	150]	Normally Open
\$109.95	SOP1204-120	1/2"	120/60	150	Brass	
\$109.95	SOP1204	1/2"	24/60	150	Diass	
\$120.45	SOP1206-120	3/4"	120/60	150		
\$126.27	SOP1206	3/4"	24/60	150		
\$112.71	SOP1208	1/8"	24/60	365		Normally Closed
\$72.12	S0P1210	1/4"	24/60	150	Stainless	
\$64.53	S0P1212-120	1/4"	120/60	145		
\$105.31	S0P1212	1/4"	24/60	145		
\$68.19	SOP1214	1/4"	24/60	120	Brass	
\$150.54	SOP1216	1/4"	24/60	130]	Normally Open
\$171.28	SOP1218	1/4"	24/60	100		Universal Operation



SOP1216





SOP1060



SKINNER SOLENOID VALVE

PARKER


PRICE	PART #	DESCRIPTION
\$153.51	SOP1040	7221GBN4VN00 Skinner Solenoid
\$226.60	SOP1060	71215SN2MV00A0J111B2 Skinner Solenoid
\$159.04	SOP1020	71335SN2KNJ1N0C111B2 Skinner Solenoid
\$159.04	SOP1000	71315SN2ENJ1N0C111P3 Skinner Solenoid
\$120.53	SOP1090	71215SN2MN00N0C111P3 Skinner Solenoid
\$91.10	SOPK320	SK000090 Seal Kit MG & MF



STEEL DIRECT OPERATED SOLENOID VALVE 1/4" NPT

SMC PNEUMATICS





- Size: 2 (Series 20)
- Body Material: S (Stainless Steel)
- Seal Material: N (NBR)
- Orifice Diameter/Port Size: 302 (Orifice Diameter: ø3.2mm; Port Size: 1/4)
- Thread Type: N (NPT)
- Rated Voltage: 3 [120 (110) VAC]
- Electrical Entry: DS (DIN Terminal, w/Surge Voltage Suppressor)
- · Bracket: None

PRICE	KR #	SMC #	PORT	VOLTAGE
\$54.93	SMC600-24	JSX21-SN302N-BCS		24 VAC
\$53.87	SMC600-24DIN	JSX21-SN302N-BDS	1/4"	24 VAC DIN
\$54.75	SMC600-120	JSX21-SN302N-3CS	74"	120 VAC
\$54.40	SMC600-120DIN	JSX21-SN302N-3DS		120 VAC DIN



• Stainless steel enclosure for superior resistance to both corrosion and water

SMC

- · Coil technology maximizes magnetic efficiency and reduces energy consumption
- Internal stopper reduces metal noise
- Standard stainless-steel body, IP67 protection rating
- 360-degree coil rotation
- . UL, CE and NSF compliant

ASCO® SOLENOID VALVES ASTO RedHa

• The solenoid is an electromagnetic part of a valve, comprised of a coil, coretube, core and enclosure. ASCO Red Hat brand solenoid valves are designed to handle the most demanding fluid control applications.



NORMALLY CLOSED LOW PRESSURE SOLENOID VALVES

ASCO RED HAT



· When no power is applied to the coil, the valve stays closed. Once power is applied the valve opens

PRICE	PART #	VOLT	PSI	PIPE	BODY
\$42.82	SA012	24		1/8"	BRASS
\$76.04	SA016	24		1/8"	STAINLESS
\$62.05	SA100	110	150	1/4"	
\$62.05	SA111	24	150	1/4"	BRASS
\$50.69	SA112	110]	1/4"	CCAND
\$50.69	SA113	24		1/4"	

PRICE	PART #	VOLT	PSI	PIPE	BODY
\$84.78	SA160	110	150	1/4"	STAINLESS
\$84.78	SA161	24	150	1/4"	STAINLESS
\$118.86	SA200	120	125	1/2"	
\$118.86	SA202	24	125	1/2"	BRASS
\$128.49	SA300	110	150	3/4"	DIVAGG
\$128.49	SA302	24	150	3/4"	



NORMALLY OPEN LOW PRESSURE SOLENOID VALVES

ASCO RED HAT



- · When no power is applied to the coil, the valve stays open. Once power is applied the valve closes
- Most commonly used for weep systems

PRICE	PART#	VOLT	PSI	PIPE	BODY
\$93.51	SA170	110	75	1/4"	
\$93.51	SA171	24	75	1/4"	Brass
\$206.30	SA216	110	125	1/2"	

PRICE	PART #	VOLT	PSI	PIPE	BODY
\$206.30	SA218	24		1/2"	
\$206.30	SA250	110	125	3/8"	Brass
\$206.30	SA252	24		3/8"	



NORMALLY CLOSED 3-WAY SOLENOID VALVES

ASCO RED HAT



These valves have three pipe connections and two orifices. When one orifice is open, the other is closed and

PRICE	PART #	VOLT	PSI	PIPE	BODY
\$109.27	SA135	120	100	1/4"	Brass

PRICE	PART #	VOLT	PSI	PIPE	BODY
\$109.27	SA136	24	100	1/4"	Brass



ASCO "S" SERIES SOLENOID VALVES

ASCO RED HAT



- · Available in Normally Closed and Normally Open constructions
- · Available either AC or DC operated with brass bodies. They come standard with DIN connection coils.


NORMALLY CLOSED								
PRICE	PART #	SIZE	VOLTS					
\$66.32	SC100	3/8"	24					
\$66.32	SC125	3/8"	120					
\$66.32	SC200	1/2"	24					
\$66.32	SC225	1/2"	120					
\$95.99	SC300	3/4"	24					
\$95.99	SC325	3/4"	120					
\$34.42	SC010	1/4"	24					
\$34.42	SC025	1/4"	120					

NORMALLY OPEN				
PRICE	PART #	SIZE	VOLTS	
\$128.71	SC250	1/2"	24	
\$128.71	SC275	1/2"	120	
\$39.55	SC015	1/4"	24	
\$128.71	SC150	3/8"	24	
\$128.71	SC175	3/8"	120	
	_			



ASCO RED HAT







- · Glass fiber reinforced polyamide housing and lid
- · IP65 protection against moisture entry and washdown when properly installed with gaskets
- LED: Light Emitting Diode. A solid-state diode that emits light to indicate power to the connector
- · VDR: Varistor absorbing the self-inductance of the coil. The VDR is there to protect the coil or controller against supply overvoltage or peak
- Maximum voltage 240 Volts

PRICE	PART #	SIZE	ROTATABLE
\$44.28	SA290410001	18mm - ½" Conduit	90°
\$55.00	SA290413001	11mm - ½" Conduit	180°





SOLENOID VALVES

DANFOSS VALVES



• Covers a wide range of direct-operated 2/2-way solenoid valves for universal use. A robust valve program with high performance and can be used in all kind of tough working conditions. The lifetime of the valve is significantly extended because of the specially shaped diaphragm that reduces the stress level of the rubber. This special shape also ensures optimal flow.

PRICE	PART #	SIZE	STYLE	VOLTS	PSI	DANFOSS #
\$50.27	DF032U758419	1/4"		24	290	32U758419
\$72.90	DF032U758519	3/8"		24		32U758519
\$79.65	DF032U758536	3/8"	Name allo Olasa d	120		32U758536
\$93.68	DF032U758619	1/2"	Normally Closed	24	145	32U758619
\$103.42	DF032U758636	1/2"		120		32U758636
\$93.72	DF032U6524	3/4"		120		032U6524

REPAIR KITS

SOLENOID VALVES

PRICE	PART #	SIZE	STYLE
\$29.80	DF032U1066	3/8"	Calanaid Banair Kit
\$34.27	DF032U1069	3/4"	Solenoid Repair Kit
\$42.24	DF032U0166	3/8"	Armatura Banair Kit
\$85.86	DF032U0167	1/2"	Armature Repair Kit

DOLE DUAL INLET

SOLENOID VALVES

• 24V coil AC • $\frac{3}{4}$ " Male Garden Hose • $\frac{3}{8}$ " Female Pipe Thread

PRICE	PART #	DESCRIPTION	
\$61.40	SOM1000	Dole Dual Inlet Valve	
\$11.06	SOM2550	Dole Valves Repair Kit	



ERIE 3-WAY SOLENOID VALVE

SOLENOID VALVES

- Erie's line of motorized hydronic valves, the PopTop, provides convenient, reliable, and easy installation for a variety of heating and cooling applications.
- The PopTop makes installation a snap with easy, one-handed removal or engagement of the actuator to the valve body.
- · Brass forged 300 PSIg rated body
- Meets or exceeds ANSI IV standard for close off
- · Wide variety of Cv's for better control

PRICE	PART #	SIZE	VOLTAGE	PSI
\$113.58	S013000	1/2"	24	20
\$137.79	S013100	3/4"	24	13



REPLACEMENT MOTOR FOR BOTH VALVES

ERIE 3-WAY SOLENOID VALVE

\$55.76 S013000M



MAC® SOLENOID

REPLACEMENT FOR POPULAR AUTOMATICS



- Unique patented MAC SOLENOID® valves for fastest possible response time with non burn-out feature on AC service
- · Balanced poppet pilot valve for high flow, precise repeatability and consistent operation
- · Large spool or piston for maximum shifting forces even and minimum operation pressure
- · MAC spool and bore combination for wiping away contamination - eliminating sticking and for use on lubricated or non-lubricated service

PRICE	PART #	MFG PART#	DESCRIPTION	VOLTAGE
\$84.22	MAC2000	811C-PP-221CA-152AD	1/4" Mac Valve 800 Series	24 Volt
\$41.59	MAC2010	111B-221CABH	Solenoid For Laser Wash	24 Volt
\$65.79	MAC2060	225B-111CA	Solenoid 3 Way	110 Volt
\$63.25	MAC2090	225B-221CA	Solenoid 3 Way	24 Volt
\$90.35	MAC2170	811CPM224JA152	Solenoid with coil and base	24 Volt
\$91.09	MAC2150	811CPM114JA152	1/4" 120V Square DIN	120 Volt
\$47.27	MAC2040	113B-224JA	100 Series Mac Valve	24 Volt
\$47.27	MAC2020	113B-114JA	1/4" 3 Way Valve with DIN	120 Volt
\$44.86	MAC2030	113B-114JJ	1/4" Mac Valve 100 Series	120 Volt
\$44.86	MAC2050	113B-224JJ	1/4" Mac Square Din Connection Male	24 Volt
\$67.71	MAC2070	225B-111JA	1/4" 3 Way with Square DIN	110 Volt
\$70.24	MAC2080	225B-114JJ	1/4" With Square Din Conncetion Male	120 Volt
\$55.09	MAC2140	46A-LOO-JACOLR	Solenid for PDQ Touchless	24 Volt
\$106.12	MAC2180	912B-PM-221CAAB	1/4" Mac Valve for Laser Wash	24 Volt
\$29.32	MAC2100	35A-AAA-DACA1BA	1/8" Mac Valve for Ryko Dryer	24 Volt
\$33.42	MAC2110	35A-AAA-DACF1BA	1/8" W/96" Wire	24 Volt
\$43.99	MAC2120	45A-AA1-DACA1BA	1/8" 4-Port	24 Volt
\$55.09	MAC2130	46A-AA1-JACO1LR	1/8" No Leads	24 Volt
\$55.09	MAC2140	46A-LOO-JACOLR	Mac Valve for PDQ G5 Laserwash	-
\$85.90	MAC2160	811CPM114CA152	1/4" with Conduit 1/2"NPS	120 Volt
\$31.92	MAC2180-KIT	K09006	Repair Kit for 912BPM221	-

SAFETY & POP OFF VALVES

STAINLESS STEEL CHECK VALVE

SAFETY & POP OFF VALVES



- Inlet: 1/4" Female Outlet: 1/4" Male
- Cracking Pressure: Less than 1 PSI
- · Material: Stainless Steel
- Max. Pressure: 5000 PSI
- . Max. Flow Rate: 4 GPM

CV0003 \$20.90



SAFETY RELIEF VALVE



- · Designed for self-cleaning of circular area chamber and piston head
- Excess pressure vented out through discharge fitting, preventing damage to pump
- · Adjustable set screw allows setting relief valve for discharge at your specific pressure
- Safety relief valves are tested but are not preset
- Stainless steel spring, brass construction
- 3/8" hose barb discharge fitting
- Max. temp.: 200°F Max. Flow: 7 GPM

\$40.46	RE7415	1500 PSI
\$40.46	RE7416	2000 PSI



POP-OFF VALVE

FLUID CONTROLS

FLUID CONTROLS

- · All models feature either machined brass or stainless steel construction
- · All lower pressure models feature resilient valves, higher pressure valves offer stainless steel valve components as standard
- Atmospheric or hose barb relief ports 1/4" to 1/2" NPTM inlet ports • Relief pressures from 750 to 6,500 PSI

PRICE	PART #	SIZE	GPM	PSI
\$9.55	RERV100	1/4"	3	1500
\$16.30	RERV500	3/8"	6	2000
\$20.68	RERV5001	3/8" with 1/4" Barb	6	2000

PRICE	PART #	SIZE	GPM	PSI
\$16.72	RERV500B	3/8"	6 GPM	3500
\$34.18	RERV600	3/8"	12 GPM	6500



THERMO VALVE SAFETY & POP OFF VALVES



- · Protects pumps from premature failure of seals, packing and cups by eliminating heat buildup in closed loop bypass systems.
- Valves open when temperature exceeds 145°F.
- Maximum pressure is 200PSI

\$13.86	TH0100	3/8"
\$13.86	TH0105	1/2"








PRICE	PART #	SIZE	PSI
\$33.13	PU30960	1/4"	300-1500
\$33.13	PU30961	1/4"	1000-3000
\$37.50	PU33960	3/8"	300-1500
\$37.50	D1133063	3/2"	1000-4000



POP-OFF VALVE


GIANT PUMPS



BALL & METERING VALVES

LONG HANDLE BALL VALVE

BALL & METERING VALVES



- · Suitable for full range of liquids and gases
- Fast ¼ turn open or close operation
- Flow can go in both directions

 Solid chrome 	plated bra	iss bal
----------------------------------	------------	---------

- · Pressure rated at 600 PSI
- · Low operating torque

\$13.39	VL0031	1⁄4" F x F
\$13.63	VL0036	3/8" F x F
\$18.12	VL0041	½" F x F

\$18.23	VL0046	3/4" F x F
\$22.44	VL0046MF	3/4" M x F





FULL PORT BALL VALVE **BALL & METERING VALVES**

· 3/8"

\$9.66 VL0032

BALL VALVES ARE BUILT TO LAST.

These durable, simply designed valves boast a long operational life and act as an ideal shut-off mechanism. Don't forget, due to their design, ball valves can crack in the event of a freeze. Consider adding heat tape to your pipes!



METERING VALVE

BALL & METERING VALVES

- Precision calibrated dial to determine and allow a return to required flow settings
- Safe positive stop for needle travels

One-piece forged housing

- · Positive no-leak stem seal · Nickel-plated available
- 1000 PSI maximum operating pressure
- · Suitable for natural gas

\$8.53	VL0001	1∕8" F x F
\$20.29	VL0002	1/8" M x M
\$7.61	VL0004	1∕8" M x F

\$11.16	VL0006	1⁄4" F x F
\$9.37	VL0007	1⁄4" M x F
\$15.23	VL0008	1⁄4" M x M

\$10.90
California wasses



FLUID CONTROLS



METERING VALVE

\$22,52 VL0015

FLUID CONTROLS

- · All adjusting knobs have oversize brass inserts with double setscrews to prevent loosening double Viton o-ring seals
- Valve bodies are either brass or stainless steel
- · Panel mount or in-line styles, hose barb or threaded ports

- 1/4" F x F

· All ad	justing	shafts	are	stainless	steel	with

- All models have flow areas equal to a .140 diameter orifice
- Valves are in-line controls where flow is locked at a specific setting



BALL VALVE

VALLEY INDUSTRIES



 PRESSURE RATING: 200 PSI (CWP) • TEMPERATURE RATING: -4°F to 250°F BODY MATERIAL: Chromed brass

• BALL MATERIAL: Chromed brass • STEM MATERIAL: Chromed brass

 SEAT MATERIAL: Teflon® • SEAL MATERIAL: Viton®

\$8.78	VL0023	1⁄4" F x F
\$8.78	VL0024	3/8" F x F
\$10.88	VL0025	½" F x F



SHORT HANDLE BALL VALVE

THE SPECIALTY MFG. CO.

THE SPECIALTY MFG

• MAXIMUM PRESSURE: MAXIMUM TEMPERATURE: 180°F

\$5.18	VL0021	1⁄4" F x F
\$5.18	VL0022	1⁄4" M x F
\$14.47	VL0026	3/8" F x F
\$14.47	VL0027	3/8" M x F
\$14.92	VL0042	1/2" F v F



BALL VALVE

GENERAL PUMP®

 MAXIMUM FLOW: 12 GPM • MAXIMUM PRESSURE: 5000 PSI

· Ideal for use in pressure washing applications!

\$43.24	VL0110	3/8" NPTF
\$65.16	VL0112	1/2" NPTF



METERING VALVE

THE SPECIALTY MFG. CO. THE SPECIALTY MFG. CO.

• THROUGH HOLE DIAMETER: .156" • SIZE: 1∕4" F x F

• MAXIMUM TEMPERATURE: 180°F • MAXIMUM PRESSURE: 500 PSI

With metering knob

\$27.48 VL0010

BOB[®]

BOB[®]

 $\mathbf{BOB}^{\mathbb{R}}$

VALVES & FLOATS

FVR400 VALVE - MIP X MIP

BOB VALVES

· High capacity - heavy duty • Adjusting arm tapped • Buna-N disc standard Red brass body

	PRICE	PART #	INLET	OUTLET	35 PSI	65 PSI	85 PSI
)	\$28.66	FVR400-6	3/8" MIP	3/8" MIP	9 GPM	11.5 GPM	13 GPM
	\$30.06	FVR400-8	1/2" MIP	1/2" MIP	12 GPM	18 GPM	22 GPM
	\$38.70	FVR400-12	3/4" MIP	3/4" MIP	21 GPM	32.5 GPM	39.9 GPM
	\$60.90	FVR400-16	1" MIP	1" MIP	43.5 GPM	61 GPM	68.5 GPM

KIT FOR PART #	PLUNGER ASSEMBLY KIT	CUP & DISC KIT	ARM KIT	STEM	VITON CUP & DISC KIT
FVR400-6	FVRKB200	FVRKB100	FVRKB300	FVR450-10	FVRKB100V
FVR400-8	FVRKB210	FVRKB110	FVRKB300	FVR450-10	FVRKB110V
FVR400-12	FVRKB220	FVRKB120	FVRKB300	FVR450-10	FVRKB120V
FVR400-16	FVRKB230	FVRKB130	FVRKB300	FVR450-10	FVRKB130V

PLUNGER ASSEMBLY KIT	ARM KIT	STEM	CUP & DISC KIT



STEMS

BOB VALVES

PRICE PART# LENGTH DESCRIPTION \$6.18 FVR450-1-6 1/4" - 20 SAE male connection - brass construction 10" x ½"-20 brass float valve stem for FVR400-6; FVR400-8; FVR400-12; FVR400-16 and BOB CASA 3/8" - 16 10~ FVR450-10 \$7.71 FVR452-10 \$15,21 \$19.16 FVR380 10" x $\frac{3}{8}$ "-16 brass float valve stem



BOB VALVES

BOB[®]

· High capacity - heavy duty · Red brass body

PRICE	PART #	DIA.	BUOYANCY IN LBS.	F SPUD CONNECTION
\$60.07	FVR440-3	3"	.34	1/4" - 20 SAE
\$48.79	FVR440-4	4"	.80	1⁄4" - 20 SAE
\$62.26	FVR440-5	5"	1.73	1/4" - 20 SAE
\$71.41	FVR440-6	6"	3.26	1⁄4" - 20 SAE
\$71.81	FVR441-6	6"	3.26	⁵ /16" - 18
\$72.05	FVR442-6	6"	3.26	3/8" - 16 SAE
\$99.25	FVR440-7	7"	5.72	3/8" FIP
\$91.99	FVR441-7	7"	5.72	5∕16" - 18 SAE
\$142.96	FVR440-8	8"	8.03	3/8" FIP



POLYPROPYLENE FLOATS

BOB VALVES

PRICE	PART #	DIA.	F SPUD CONNECTION	BUOYANCY IN OZS.
\$14.66	FVPF5	5"	1/4" - 20	34.7
\$17.30	FVPF6	6"	1/4" - 20	61
\$17.30	FVPF6-7	6"	⁵ ⁄16" - 18	61
\$20.25	FVPF8	8"	3/8" FIP	158

California WARMING





FVRC810 CASA VALVE

BOB VALVES

 Free Flow Outlet · For high heat

PRICE	PART #	INLET	35 PSI	85 PSI	California WARNERS
\$32.50	FVRC810-6	3/8" MIP	9 GPM	13 GPM	
\$40.31	FVRC810-8	1∕2" MIP	14 GPM	22.5 GPM	
\$55.13	FVRC810-12	3/4" MIP	27 GPM	36 GPM	
\$78.87	FVRC810-16	1" MIP	80 GPM	138 GPM	

KIT FOR PART #	PLUNGER ASSEMBLY KIT	ARM KIT	STEM	VITON CUP & DISC KIT
FVRC810-6	FVRKB233	FVRKB333	FVR450-10	FVRKB133V
FVRC810-8	FVRKB233	FVRKB333	FVR450-10	FVRKB133V
FVRC810-12	FVRKB236V	FVRKB333	FVR450-10	FVRKB136V
FVRC810-16	FVRKB239V	FVRKB339	FVR450-10	FVRKB139V

California WARNING PROPOSITION 65

BOB[®]

KIT FOR PART #	PLUNGER ASSEMBLY KIT	ARM KIT	STEM	& DISC KIT
FVRC810-6	FVRKB233	FVRKB333	FVR450-10	FVRKB133V
FVRC810-8	FVRKB233	FVRKB333	FVR450-10	FVRKB133V
FVRC810-12	FVRKB236V	FVRKB333	FVR450-10	FVRKB136V
FVRC810-16	FVRKB239V	FVRKB339	FVR450-10	FVRKB139V



FLOAT VALVES

TOPAZ INDUSTRO FLOAT VALVE

 Topaz Industro Float Valves are designed to maintain water levels in applications requiring a valve with high mechanical strength and heat resistance, like industrial storage tanks and heated water cisterns

Compact robust construction

Made from corrosion-resistant materials

Comes complete with float and arm

Has a switch to lock valve in off position

· Has an internal filter to keep debris out of the valve

· Shuts down slowly to minimize water hammer

Mounts horizontally or vertically

· Has port to connect to Frostpro anti-freeze device

FOR HOT WATER

MOUNTS ABOVE OR BELOW WATER

JFVT12 3/4" Valve \$231.22 JFVT16 1" Valve


• WATER DIFFERENTIAL: 3/4" - 2 1/2" increases as water inlet pressure increases

 VALVE BODY: Grivory • WHITE INTERNAL PARTS: TE21 Acetal • FILTER: PP/Nylon • DIAPHRAGM: **FPDM** • VALVE SEAL: Santoprene

• SPRINGS, BOLTS, NUTS PIN, SCREW: 304 Stainless Steel

• 0-RINGS: Nitrile • FLOAT: **HDPE** • FLOAT CORD: Polyster • MAX OPERATING TEMP.: 176°F • PRESSURE RATING: 5-100 PSI • FLOW: Up to 90 GPM

\$44.89 **JFVTIK** Service Kit



IORE VALVES

• Shuts down slowly to minimize water hammer

· Has port to connect Frostpro anti-freeze device

· Comes complete with float and arm

· Has a switch to lock valve in off position

· Has an internal filter to keep debris out of the valve

Float position easily adjustable without tools

· High flow

· Made from corrosion-resistant materials

Mounts horizontally or vertically

MOUNTS ABOVE OR BELOW WATER

WATER DIFFERENTIAL:

3/4" - 2 1/2" increases as water inlet pressure increases

 VALVE BODY & TAIL: Glass filled nylon

WHITE/YELLOW

INTERNAL PARTS: Acetal • FILTER: PP/Nvlon • DIAPHRAGM: **EPDM** · SEAL: TPU


• SPRINGS, BOLTS, NUTS

PIN, SCREW: 304 Stainless Steel

• 0-RINGS: Nitrile FLOAT: HDPF • FLOAT CORD: Polyester • MAX OPERATING TEMP.: 140°F • PRESSURE RATING: 5-100 PSI Up to 90 GPM • FLOW:

\$86.58	JFVTS12	3/4" Valve	\$86.23	JFVTS18	11/4" Valve
\$85.05	JFVTS16	1" Valve	\$18.66	JFVSTK	Service Kit

TOPAZ DIFFERENTIAL VALVE IORE VALVES



• Powered entirely by the water pressure/water level in the tank. It reduces the cycling wear and tear on the pump, and energy wasted when pumps turn off/on prematurely.

· Has a switch to lock valve in off position

· Has an internal filter to keep debris out of the valve

 VALVE BODY: Glass Filled Nylon • WHITE/YELLOW INTERNAL PARTS: Acetal • FILTER: PP/Nvlon

• DIAPHRAGM: **FPDM** • SEAL: Urethane

• SPRINGS, BOLTS, NUTSPIN, SCREW: 304 Stainless Steel

• 0-RINGS: Nitrile • FLOAT: **HDPE** FLOAT CORD: Polyster • ACTUATOR ARMS/CAPS: ABS • MAX OPERATING TEMP.: 140°F • PRESSURE RATING: 15-150 PSI • FLOW: Up to 90 GPM

\$244.30 JFVD12 3/4" Valve **MOUNTS ABOVE WATER** \$246.36 JFVD16 1" Valve



TOPAZ VALVE OUTLET EXTENSION

JOBE VALVES

· Detachable outlet extension is designed to fit over the existing outlet on your Topaz valve with detachable base. The outlet extension directs the flow into a narrow stream creating a less turbulent water flow. This product lengthens the outlet by 2"

• User can glue in a longer piece of 1" PVC pipe extending the outlet as far as they like

• Extends outlet 2"

• Built-in air break non-siphon

Fits Topaz valves with detachable base

· Converts oval outlets to round outlets

• SCREWS: Stainless steel (holds outlet in place)

• MATERIAL: PVC

• MAXTEMP: 140°F

NOT FOR USE WITH HOT WATER -DO NOT USE WITH TOPAZ INDUSTRO

\$10.11 JFVP50



FLOAT VALVES



VORTEX FLOAT VALVE

JOBE VALVES

- High flow
- · Compact robust construction
- Mounts horizontally
- Corrosion-resistant materials
- · Shuts down slowly to minimize water hammer
- Float position easily adjusts w/o tools
- · Valve unscrews from tail for easy valve seal access
- Switch for locking in "off" position
- · Has port to connect to Frostpro anti-freeze device

• WATER LEVEL DIFFERENTIAL: 3/4" - 21/2" • PRESSURE RATING: 5-100 PSI • VALVE BODY: **GF** Nylon • WHITE INTERNAL/EXTERNAL: Acetal • ARM ASSEMBLY: ABS • DIAPHRAGM: **EPDM** • SEAL: Urethane

• METAL HARDWARE: 304 Stainless Steel

• 0-RINGS: Nitrile FLOAT: **HDPE** • MAX OPERATING TEMP.: 140°F

MOUNTS ABOVE WATER

\$280.25	JFVV20	11/4" Valve
\$287.41	JFVV24	1½" Valve
\$291.51	JFVV32	2" Valve



ROJO FLOAT VALVE

JOBE VALVES

- · Mounts above or below water level
- · May be placed on side, bottom, or top of water tanks and troughs
- Easy to service just unscrew the parts!
- Fully adjustable float arm
- · Made with corrosion-resistant materials
- · Includes backnut and seal washer
- · Built-in check valve
- Includes switch to lock valve in off position
- Flow automatically stops during servicing

MOUNTS ABOVE OR BELOW WATER

\$32.85	JFVR08	½" Valve
\$33.88	JFVR12	3/4" Valve



ARMS INTERNAL BLACK **MOLDINGS:**

• SEAL WASHER: LDPE

• METAL HARDWARE: 304 Stainless Steel

• 0-RINGS: Nitrile

 MAX OPERATING TEMP.: 140°F



ROJO COMPACT FLOAT VALVE

JOBE VALVES

- · Fits in compact spaces
- Float no wider than valve
- Multiple mounting positions side, bottom, and top
- Fully adjustable float
- · Non-corrosive material
- · Flow stops when unscrewed
- · Valve body screws apart by hand for easy servicing
- Flow stops when unscrewed for servicing
- Supplied with backnut and seal washer
- · Built-in check valve
- · Fully adjustable float angle

MOUNTS ABOVE WATER

\$34.91	JFVR08-C	½" Valve
\$35.42	JFVR12-C	3/4" Valve



0-150 PSI max VALVE BODY TAIL & NUT: ABS

• YELLOW PARTS/FILTER: Acetal **HDPE**

FLOAT: ARM EXTENSION ARMS

INTERNAL BLACK MOULDINGS: Glass Filled nylon I DPF

• SEAL WASHER:

• METAL HARDWARE: 304 Stainless Steel

• 0 RINGS:

Nitrile

• HIGH FLOW SEAL: Urethane • FLOAT CORD: Polyester

• MAX OPERATING TEMP.: 140°F




Glass filled nylon



FLOAT VALVES







- functional life • A 2 ½" float is all that is required to shut off the 1 ½" valve
- 1- piece urethane diaphragm
- 1/2" red plastic pilot valve
- 1" FPT inlet and outlet pipe size
- 4" float diameter

• PRESSURE RANGE: 5-110 PSI

Up to 250 GPM @ 60 PSI • FLOW:

\$42.53	FVC16	Stage 2 - 1" Float Valve with Pilot
\$76.52	FVC24	Stage 2 - 1 ½" Float Valve with Pilot

S3-100 STAGE 3 VERTICAL FLOAT VALVE WITH PILOT





• Designed for use in high turbulent tank conditions requiring 3/4" water level change before activations

DIMENSIONS: 9" x 9" x 3 1/4" • PRESSURE RANGE: 5-110 PSI · PORT: 1" FPT inlet/outlet

\$47.99 FVC16-3

CLEVELAND

Stage 3 - 1" Vertical Float Valve w/Blue & White Pilot



S4-100 STAGE 4 FLOAT VALVE WITH REDUNDANT BACK UP

CLEVELAND



- Features a smooth positive shutoff with redundant backup
- Two float valves in one! If the primary valve fails, the backup takes over.
- · Provides no more flooded pump rooms or high water/sewer bills

• DIMENSIONS: 9" x 14 ½" x 6 ¼" • PRESSURE RANGE: 5-110 PSI • PORT:

1" FPT inlet/outlet

\$84.27 FVC16-4 Stage 4 - 1" Float Valve with Redundant Back Up



FLOAT VALVE DIAPHRAGM FOR 100 SERIES VALVES CLEVELAND

CLEVELAND

\$8.75 FVC71D Diaphragm Only



FLOAT VALVE

WALTERS



- "Lo Valve" kicks in when a small amount of water is needed. When valve completely opens, the "Main Valve" is activated. Designed for car & truck washing.
- Features two interacting valves
 RATED TO 140°F

VALVES				
PRICE	PART #	DESCRIPTION	GPM	
\$41.25	FVW08	½" with float	13 GPM @ 80 PSI	
\$43.20	FVW12	3/4" with float	21 GPM @ 80 PSI	
\$70.63	FVW16	1" with float	100 GPM @ 80 PSI	

PARTS			
PRICE	PART #	DESCRIPTION	
\$19.10	FVWP150	Pilot Valve Assembly	
\$13.13	FVWP16D	Diaphragm for 1"	
\$0.30	FVWP17	Conical Spring 1/2" - 3/4"	
\$0.40	FVWP18	Conical Spring 1"	
\$9.92	FVWP812D	Diaphragm for $\frac{1}{2}$ " - $\frac{3}{4}$ "	

FLOAT VALVES & PREVENTERS



HUDSON HIGH TEMPERATURE

• The unique patented design of the Hudson Valve uses fluid pressure, as opposed to a lever arm and ball, as the force to close the valve. This compact, self-contained design greatly enhances the valve's reliability. The valve body is made of durable glass-filled nylon 6/6. Internal parts are of ABS plastic, silicone, and stainless steel. When properly installed, the valve will meet anti-siphon requirements.

\$30.32	FVH08	½" Valve
\$30.32	FVH16	1" Valve
\$15.32	FVHK4HT	Repair Kit for FVH16
\$15.32	FVHK4HTS	Repair Kit for FVH08
\$2.49	FVHP09N	Filter for 1" Valve

\$8.87	FVHP01	Valve Cap for 1" Valve
\$2.22	FVHP03	Retainer Ring
\$6.20	FVHP05	Control Diaphragm for 1" Valve
\$14.54	FVHP06	Valve Body (New Style)
\$6.90	FVHP07	Float Body for 1" Valve



FLOAT VALVE

SUTTNER



- Brass 1/2" valve with plastic float
- Float rod is 61/2" long
- Inlet port is ½" FPT





FLOAT VALVES

WATTS



\$136.15	FVW1000	1" Float Valve
\$38.11	FVW500	½" Float Valve
\$84.84	FVW750	3/4" Float Valve



COMPLETE PLUNGER ASSEMBLIES

• 175°F, max, temperature

Max. flow 5 GPM

WATTS

WATTS

\$24.38	FVWP186	1/2" Assembly
\$33.40	FVWP187	3/4" Assembly
\$40.52	FVWP188	1" Assembly



175 PSI BACKFLOW PREVENTER

WATTS



- · Prevent reverse flow of polluted water from entering into potable water supply due to backsiphonage and/or backpressure
- · Now Lead Free! Bronze body construction, bronze ball valve shutoffs, and bronze test cocks
- · Air-in/water-out design principle for protection during emergency combined backsiphonage and backpressure conditions

\$383.71	WBF009QT12	3/4" Without Strainer
\$360.74	WBF009QT16	1" Without Strainer
\$768.17	WBF009QT24	1½" Without Strainer
\$991.81	WBF009QT32	2" Without Strainer
\$450.91	WBF009QTS12	3/4" With Strainer
\$509.07	WBF009QTS16	1" With Strainer
\$1.993.37	WBF9090T16	1" Without Strainer

\$1,673.21	WBF909QT12	3/4" Without Strainer
\$3,679.76	WBF909QTS32	2" With Strainer
\$3,270.53	WBF909QTS24	1½" With Strainer
\$2,357.56	WBF909QTS16	1" With Strainer
\$2,012.23	WBF909QTS12	3/4" With Strainer
\$310.89	WBF909K	Repair Kit



NOW LEAD FREE!

MAXI FLOW





- Designed for operations with minimal restriction
- · Positive check. No leaks. Pressure drop is insignificant.
- · Stainless steel poppet and spring
- · Viton seal
- Less than 1 PSI cracking pressure
- Completely repairable
- Temperature rating to 200°F
- Flow Rate: 4 GPM

PRICE	PART #	PRESSURE	SIZE
\$18.22	CV0006	5000 PSI	1/4" F x F SS HP
\$5.35	CV0006K	2000 PSI	1/4", 3/8" Repair Kit
\$14.39	CV0009	3000 PSI	1/4" F x F Brass
\$15.34	CV0039	3000 PSI	3/8" F x F Brass

CHECK VALVES



POLYPROPYLENE CHECK VALVES

THE SPECIALTY MFG. CO.

THE SPECIALTY MFG. CO.

PRICE	PART #	SIZE	MAX PSI/ OPENING PSI
\$9.08	CV0072	½" F x F	125 PSI / 1-3 PSI
\$10.31	CV0073	3/4" F x F	125 PSI / 1-3 PSI

PRICE	PART #	SIZE	MAX PSI/ OPENING PSI
\$8.51	CV0074	3/8" F x F	125 PSI / 1-3 PSI
\$8.08	CV0082	1⁄4" F x F	125 PSI / 1-3 PSI



BRASS CHECK VALVE

THE SPECIALTY MFG. CO.

THE SPECIALTY MFG. CO

• All brass body • Stainless steel spring • Buna seal O-ring poppet seal for bubble-tight operation • Repair kit not available

PRICE	PART #	SIZE	MAX PSI/ OPENING PSI
\$8.40	CV0035	1⁄4" F x F	1200 PSI/ 3 PSI
\$10.12	CV0040	3/8" F x F	1200 PSI/ 3 PSI
\$12.79	CV0045	1/2" F x F	1200 PSI/ 3 PSI



PVC HOSE BARBS

THE SPECIALTY MFG. CO.

PRICE	PART #	SIZE	MAX PSI/ OPENING PSI
\$6.18	CV0061	1∕4" M x M	125 PSI/ 1 - 3 PSI
\$8.17	CV0063	1/4" barb x 3/8" barb	125 PSI/ 1 - 3 PSI
\$6.18	CV0064	1/4" M x 1/4"Barb	125 PSI/ 1 - 3 PSI
\$6.18	CV0065	1/4" Check Valve	125 PSI/ 1 - 3 PSI
\$6.18	CV0066	3/8" Check Valve	125 PSI/ 1 - 3 PSI

\$16.69 CV0004 1/4" M x M \$5.35 CV0006K

PRICE	PART #	SIZE	MAX PSI/ OPENING PSI
\$6.18	CV0067	½" Check Valve	125 PSI/ 1 - 3 PSI
\$6.18	CV0068	½" x 3/8" Check Valve	125 PSI/ 1 - 3 PSI
\$6.18	CV0069	1⁄4" F x F	125 PSI/ 1 - 3 PSI
\$6.18	CV0070	1∕4" F x M	125 PSI/ 1 - 3 PSI



LOW PRESSURE CHECK VALVE

Stainless steel construction

Maximum flow rate 4 GPM

KLEEN-RITE

- Maximum Pressure 2000 PSI
- Maximum Temperature 200°F
- KIEEN-RITE CORP. • Opening pressure less than 1 PSI
- Standard with EPR seal for chemical resistance

Repair Kit



LOW PRESSURE CHECK VALVE

KLEEN-RITE

KIEEN-RITE CORP.



NVALUE LINE

KIEEN-RITE CORP.

· Use in tank and inlet applications

\$19.95	CVK08L Brass	½" F x F 2½" L
\$29.66	CVK12L Brass	3/4" F x F 21/8"L
\$57.26	CVK12SS	3⁄4" F x F



• 1/4" F x F • 1200 PSI

\$14.52	CVV04	Brass
\$28.40	CVV04SS	Stainless Steel





BRASS CHECK VALVES

KLEEN-RITE

• Low Cracking Pressure • Bubble Tight



PRICE	PART #	PRESSURE	SIZE
\$5.56	CVS410SP	Spring for 1/4", 3/8"	
\$60.24	CVB810	½" Brass	
\$81.43	CVB812	3/4" Brass	



STAINLESS STEEL CHECK VALVES

KLEEN-RITE

• Low Cracking Pressure • Bubble Tight

PRICE	PART #	PRESSURE	SIZE
\$55.07	CVS410	2000 PSI	1∕4" F x F
\$2.19	CVS410K	Repair Ki	t 1/4", 3/8"
\$7.85	CVS410P	Poppet fo	r 1/4". 3/8"

PRICE	PART #	PRESSURE	SIZE
\$61.05	CVS610	2000 PSI	3/8" F
\$5.56	CVS410SP	Spring for	1/4", 3/8"

CHECK VALVES



HIGH PRESSURE CHECK VALVES

THE SPECIALTY MFG. CO.

THE SPECIALTY MFG. CO

• Maximum - 3000 PSI

\$16.76	CV0031	3/8" F x F
\$17.38	CV0030	1/4" F x F



BRASS BALL CHECK VALVE

THE SPECIALTY MFG. CO.

THE SPECIALTY MFG. CO.

- · With stainless steel ball & seat
- · Will not seal under low pressure
- Repair kit not available
- 2500 PSI

\$7.32	CV0038	1⁄4" M x M
\$6.95	CV0037	1⁄4" M x F



1/4" M x M BRASS CHECK VALVE

CVI

- 0-800 PSI
- Low Cracking Pressure
- Brass
- · Viton o-ring

\$31.16 CVC2232



34" F x F BRASS CHECK VALVE

PARKER ->a

- · Use in automatic applications
- High pressure

\$866.92 CV0085



1/4" M x M BRASS CHECK VALVE

U.S. PARA PLATE

- 0-2000 PSI
- Brass
- Viton o-ring
- Low cracking pressure of 2-5 PSI

\$15.97 CV0010



BLUE FOOT VALVE

FOOT VALVES

- For All HydroMinder Models: 506, 511, 5111, 515, 561, 562, 525, & 530
- Blue, Viton for use with whitewalls, butyl and alkali
- Corrosion-resistant plastic and rubber last longer
- Step-down hose barb 1/4"-3/8"-1/2"

\$12.62	IN250020	Single
\$120.55	IN250020-10	10 Pack



GRAY FOOT VALVE

FOOT VALVES

- For soap & wax (EPDM Seal)
- Polypropylene
- $\frac{1}{4}$ ", $\frac{3}{8}$ " and $\frac{1}{2}$ " barbs
- HydroMinder replacement part

\$9.25	IN250100	Single
\$88.32	IN250100-10	10 Pack



1/4" FOOT VALVE WITH CHECK STRAINER

DEMA

DEMA

- Step-down hose barb allows for use of the following tube sizes (outer diameter): 1/4", 3/6", 1/2"
- Poly body with stainless steel ball and EP o-ring

\$3.53 INDP10011P

California WARMING PROPOSITION 65



FOOT CHECK VALVE

FOOT VALVES

¼" Brass

\$4.62 INFBS4



FOOT VALVE STRAINER

FOOT VALVES

• 1/4" 60 Mesh

\$7.46

INHB500



STAINLESS STEEL STRAINER

DEMA

DEMA

\$5.37	INDP10011	1/4"
\$6.94	INDP3610	3/8"

California www.



½" PVC BARBED CHECK VALVE

THE SPECIALTY MFG. CO. THE SPECIALTY MFG. CO. Cotton in Our Special Country MFG. CO.

· With stainless steel strainer

\$6.18	CV0067	Check Valve
\$3.80	IN010	Strainer



½" PVC BARBED INLINE CHECK VALVE

FOOT VALVES

Viton

\$11.13 IN10076303



1/2" PVC BARBED INLINE CHECK VALVE

FOOT VALVES

• EPDM

\$8.48 IN10076304

CHECK VALVES



¾" FX F STAINLESS STEEL CHECK VALVE

CHECK VALVES

• Use in high-pressure automatic applications

\$41.20 CV0080



1/2" F X F STAINLESS STEEL **CHECK VALVE**

CHECK VALVES

• Use in high-pressure automatic applications

\$47.90

CV0075



BRASS HIGH PRESSURE CHECK VALVE

PARKER VALVES

- · Brass construction • Maximum 2000 PSI
- 8 GPM · Repair kit not available

\$22.17	CV0005	1∕8" F x F	3 GPM
\$22.15	CV0036	1⁄4" F x F	5 GPM
\$44.41	CV0043	3/8" F x F	8 GPM
\$63.61	CV0048	3/4" F x F	25 GPM



HIGH PRESSURE BRASS CHECK VALVES

U.S. PARA PLATE

- · High reliability
- · Easy to maintain
- · Low opening pressure
- 0 3000 PSI

THE SPECIALTY MFG. CO.

• 1/4" F x F

\$44.09 CV0008



INLINE CHEMICAL CHECK VALVE

THE SPECIALTY MFG. CO.

· Black/clear PVDF body and Viton seals


- 1/4" barb diaphragm connections
- Max Pressure: 125 PSI
- Max Temperature: 150°F

\$2.89	CV0100-04	1/4"
\$2.89	CV0100-06	3/8"



HIGH PRESSURE CHECK VALVES

U.S. PARA PLATE



- · Allows free-flow in one direction. Seat design protects 0-ring seal from contamination or flow damage
- Install in any position
- Temp. range -20° to +400°F. Opens at 3 to 5 PSI
- Viton seal with stainless steel spring
- · Handles water, oil and many other fluids

\$48.13	CV0011	1/4" F x F Brass
\$60.96	CV0011SS	1/4" F x F Stainless Steel
\$4.67	CV0011K	$\frac{1}{4}$ " F and $\frac{3}{8}$ " F Repair Kit
\$51.56	CV0015	3/8" F x F Brass

\$92.99	CV0022	1/2" F x F HP Brass
\$5.67	CV0022K	½" F x F Repair Kit
\$151.20	CV0051	3/4" F x F Brass
\$7.33	CV0051K	3/4" F x F Repair Kit



CHECK VALVE

FLUID CONTROLS

FLUID CONTROLS

- Constructed of stainless steel, with a Viton O-ring for leak-proof operation
- · Valves are completely rebuildable
- Maximum of 3500 PSI
- · Specifically designed for all car wash chemicals

\$19.45	CV0013	1/4" F x F Viton SS HP
\$7.91	CV0013K	1/4" SS Repair Kit
\$19.60	CV0013T	1/4" F x F Teflon HP
\$8.14	CV0013TK	1/4" Teflon Repair Kit
\$25.21	CV0041	3/8" F x F SS
\$8.72	CV0041K	3/8" F x F SS Repair Kit
\$25.35	CV0041T	3/8" Teflon SS HP

\$8.87	CV0041TK	3/8" Teflon Repair Kit
\$31.78	CV0071	½" F x F SS
\$32.64	CV0071T	1/2" F x F SS w/ Teflon seat
\$8.87	CV0071TK	½" Teflon Repair Kit
\$41.20	CV0080	3/4" F x F SS Viton
\$44.43	CV0080T	3/4" F x F SS Teflon
\$14.59	CV0080TK	3/4" Teflon Repair Kit